



Russellstoll Control Circuit Connector T&B Catalog Number:

SKR12G 70891719000

UPC Number: 708917 Status: Active

Description:

Multi-pin Receptacle, 11 Pole 12 Wire, Type SK

F	_	9	4		r	_	c
Г	ㄷ	а	u	u	ш	ㄷ	÷

Features	
	Generous Wiring Space
	Ground contacts "make first" and "break last."
Application	
	Designed for indoor or NEMA 1 automatic press, tool control and welder applications requiring rugged, shock-resistant devices capable of safely interrupting rated currents under load.
	Automotive/Industrial Interlock systems were designed for the needs of the manufacturing industry. These devices are used where safety requirements mandate a mechanically interlocked system for connectino and removal of plugs under full load.
	Designed for indoor or NEMA 1 automatic press, tool control and welder applications requiring rugged, shock-resistant devices capable of safely interrupting rated currents under load.
General	
Style	Type SK Multi-pin Receptacle
Material	Receptacle housing made of Heavy-gauged steel, plated.
Material_1	Furnished with Neoprene gasket and stainless steel 6-32 mounting screws.
Frequency	60 Hz
Amperage	20 Amp
Pole/Wire	11P/12W
System	Control Circuit & Industrial Interlock
Dimension Information	
Overall Dimensions	Available on Website
Specifications	
NEMA Rating	1
Voltage	600 Volts AC (Maximum Rating)/250 Volts DC
Packaging	
Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	120 lbs. per 100
Application Support	
Overview	Available on Website
Russellstoll Application Guide	Available on Website
Notes	





Plugs and connectors can be furnished with adapters to accommodate rigid conduit or standard connectors for armored and non-metallic cable or flexible conduit.

Certifications

RoHS Compliance

No

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com