ACCEPTED MANUSCRIPT • OPEN ACCESS

Engineering the spin polarization of one-dimensional electrons

To cite this article before publication: Chengyu Yan et al 2018 J. Phys.: Condens. Matter in press https://doi.org/10.1088/1361-648X/aaa7ce

Manuscript version: Accepted Manuscript

Accepted Manuscript is "the version of the article accepted for publication including all changes made as a result of the peer review process, and which may also include the addition to the article by IOP Publishing of a header, an article ID, a cover sheet and/or an 'Accepted Manuscript' watermark, but excluding any other editing, typesetting or other changes made by IOP Publishing and/or its licensors"

This Accepted Manuscript is @ 2018 IOP Publishing Ltd.

As the Version of Record of this article is going to be / has been published on a gold open access basis under a CC BY 3.0 licence, this Accepted Manuscript is available for reuse under a CC BY 3.0 licence immediately.

Everyone is permitted to use all or part of the original content in this article, provided that they adhere to all the terms of the licence https://creativecommons.org/licences/by/3.0

Although reasonable endeavours have been taken to obtain all necessary permissions from third parties to include their copyrighted content within this article, their full citation and copyright line may not be present in this Accepted Manuscript version. Before using any content from this article, please refer to the Version of Record on IOPscience once published for full citation and copyright details, as permissions may be required. All third party content is fully copyright protected and is not published on a gold open access basis under a CC BY licence, unless that is specifically stated in the figure caption in the Version of Record.

View the article online for updates and enhancements.

C. Yan^{1,2}, S. Kumar^{1,2}, K. Thomas^{1,2}, P. See³, I. Farrer⁴, D. Ritchie⁵, J. Griffiths⁵, G. Jones⁵, M. Pepper^{1,2}

- 1 London Centre for Nanotechnology, 17-19 Gordon Street, London WC1H 0AH, United Kingdom
- ²Department of Electronic and Electrical Engineering, University College

London, Torrington Place, London WC1E 7JE, United Kingdom

- ³National Physical Laboratory, Hampton Road, Teddington, Middlesex TW11 0LW, United Kingdom
- ⁴Department of Electronic and Electrical Engineering, University of Sheffield, Mappin Street, Sheffield S1 3JD, United Kingdom
- 5 Cavendish Laboratory, J.J. Thomson Avenue, Cambridge CB3 OHE, United Kingdom

E-mail: uceeya3@ucl.ac.uk

Abstract. We present results of magneto-focusing on the controlled monitoring of spin polarization within a one-dimensional (1D) channel, and its subsequent effect on modulating the spin-orbit interaction (SOI) in a 2D GaAs electron gas. We demonstrate that electrons within a 1D channel can be partially spin polarized as the effective length of the 1D channel is varied in agreement with the theoretical prediction. Such polarized 1D electrons when injected into a 2D region result in a split in the odd-focusing peaks, whereas the even peaks remain unaffected (single peak). On the other hand, the unpolarized electrons, achieved by reducing the effective length of the 1D channel, do not affect the focusing spectrum and the odd and even peaks remain as single peaks, respectively. The split in oddfocusing peaks is evidence of direct measurement of spin polarization within a 1D channel, where each sub-peak represents the population of a particular spin state. Confirmation of the spin splitting is determined by a selective modulation of the focusing peaks due to the Zeeman energy in the presence of an in-plane magnetic field. We suggest that the SOI in the 2D regime is enhanced by a stream of polarized 1D electrons. The spatial control of spin states of injected 1D electrons and the possibility of tuning the SOI may open up a new regime of spin-engineering with application in future quantum information schemes.

Introduction

There is considerable interest in utilizing the spin of electrons in future quantum information schemes. The use of semiconductors in this regard, with their flexibility, is particularly important both for spintronics and future information processing. The spin degree of freedom can most easily be monitored when electrons are restricted to lower dimensions and in terms of this the confinement of electrons to twodimensions (2D) with their concentration controlled by a gate is extremely useful for such investigations. Although, the GaAs electron gas is one of the cleanest semiconductor systems with relatively small spinorbit interaction (SOI), there are a few intriguing reports on the observation of the spin Hall effect[1, 2]. Additionally, some early work probed a zero magnetic field splitting in GaAs by means of the election spin resonance[3], Raman scattering[4] and Shubnikov-de Haas (SdH) oscillations[5]. In these investigations, the origin of the zero-field splitting was confirmed to be due to SOI[4, 5, 6] and the extracted strength of the SOI was greater than expected. These observations are encouraging and could open a new field of spinengineering or spintronics using electrons in GaAs which has not received much attention due to the stronger effects being present in the Indium based compounds such as InGaAs or InSb[7, 8, 9].

Although materials with strong-orbit interaction have been studied extensively for possible spintronics application [7, 8, 9], they generally suffer from relatively low mobility and short spin-relaxation time. These limiting factors can be overcome by using high mobility 2DEG in GaAs with sufficiently long spin relaxation time [10]. In addition, having a control on spin polarsation and the SOI provides an added advantage for the GaAs electron gas to have potential applications in future spin based quantum schemes.

In the present work, we report a controlled method to generate polarized electrons within a 1D channel, and measure the degree of polarization and its subsequent effect on the spin-orbit interactions in the 2D system. We have utilized transverse electron focusing which has been proven to be a useful method in measuring the population of spin states [11, 12, 13, 9, 14, 15, 8]. We found that a large SOI (in terms of the 2D GaAs electron gas) is realized by injecting partially spin polarized current from a 1D channel while a negligible SOI is obtained with unpolarized current injection. Moreover, the observation is also important for the phenomena where spin injection is involved such as the spin Hall effect[1, 2] and injection from magnetic contacts [16, 17]. This technique of modulating the spin orbit interaction may be implemented in other systems by sending a polarised current with the assistance of 1D quantum wire realised by a pair of split gates, and




Figure 1. The experiment setup and device characteristic.(a) A representative result of orthogonal focusing geometry for 90° QPC; here V_{cc} is the voltage drop across the detector. Periodic focusing peaks are well defined and the position is in good agreement with calculated value as highlighted by the arrows. Odd numbered focusing peaks show pronounced splitting, whereas even ones do not split. Upper and lower inset show the experiment setup for the 90° and 60° QPC, respectively. The light golden pattens at the end of the mesa are Ohmic contacts, the dark vellow blocks within the mesa are electron-beam lithographically defined metallic-gates. Lithographically defined separation between the injector and detector is 1.5 μ m (along the diagonal direction). The width (confinement direction) of the QPC is 500 nm (for 30° and 60° QPCs, the width is measured at the narrowest end) and the length (current flow direction) is 400 nm. The gap between the injector and detector is 200 nm, so when the injector and detector are operational, this gap remains in the pinched-off, thus fully reflecting the incident electrons. (b) A representive result from the linear focusing geometry with a separation between the injector and detector of 1.6 μ m. Inset shows the experimental setup for the linear focusing geometry.

enhancement in the SOC may be seen by measuring the split in of focusing peaks.

Experimental

The devices studied in the present work were fabricated from the high mobility two dimensional electron gas (2DEG) formed at the interface of GaAs/Al_{0.33}Ga_{0.67}As heterostructures. At 1.5 K, the measured electron density (mobility) was 1.80×10^{11} cm⁻² (2.17×10^6 cm²V⁻¹s⁻¹), corresponding to a mean free path over 10 μ m which is much larger than the electron propagation length in this work. The experiments were performed in a cryofree dilution refrigerator with an electron temperature of 70 mK, unless specified, using standard lockin technique. The results were reproducible with thermal cycling.




Figure 2. Focosuing spectrum with different injector QPC. (a)-(c) show the focusing results as a function of injector conductance for 90°, 60° and 30° QPC, respectively. Data have been offset vertically for clarity. The top (bottom) trace shown by the red (blue) arrow corresponds to the injector conductance shown in the right-panel in (a)-(c).

In the devices used here the injector and detector are defined with angled QPCs (quantum point contact, which is a short quantum wire) as shown in inset of Fig. 1 in both orthogonal (upper pane, (a)) and linear configuration (lower panel. (b)). The injector and detector QPCs are at right angle to each other forming orthogonal focusing geometry, and the shape of the QPCs has been varied from 30°-90° in steps of 30° to change the effective length along the transport direction (for example, two different shapes, 90° and 60° are shown in the inset in Fig. 1(a)). By biasing the injector and detector independently and symmetrically, we made sure that a lateral electric field across the quasi-1D injector channel was not present as this could affect the focusing process, for instance resulting in a shift of focusing peaks due to the change of the effective separation between injector and detector. The effect was reproducible in different samples and in different focusing device geometries.




Figure 3. Robustness of peak splitting under different experimental condition. Results in (a)-(d) were obtained from orthoganal focusing device with 90° QPCs. (a) Splitting of the first focusing peak was observed with the injector conductance fixed at G_0 , however, a single broad peak was observed when the injector conductance was set to $3G_0$ and $4G_0$, respectively. (b) and (c), the injector QPC was asymmetrically biased while the detector was symmetrically biased. Both the injector and detector are fixed at G_0 . The splitting of focusing peak was still observable after shifting the channel laterally by - 0.2 and - 0.4 V, respectively. A change in the position of both sub-peaks is noticed. (d) Splitting of the first focusing peak is still observable while the residual peaks weakened significantly after illuminating the device with a red LED. Data have been offset vertically for clarity.

Results and discussion

In the presence of a small positive transverse magnetic field B_{\perp} electrons are focused from injector to detector leading to focusing peaks periodic in B_{\perp} with a periodicity of 60 mT using the relation[14, 18],

$$B_{focus} = \frac{\sqrt{2}\hbar k_F}{eL} \tag{1}$$

There is good agreement between the experimental and calculated values. Here e is the elementary charge and \hbar is the reduced Planck constant, L is the separation between injector and detector. The pre-factor $\sqrt{2}$ accounts for the orthogonal focusing geometry. A comparison between negative and positive magnetic field focusing result suggests the Quantum Hall effect and Shubnikov-de Haas (SdH) oscillations are negligible in the regime of focusing[18], and all the features are due to transverse electron focusing only. Apart from the well resolved focusing peaks as shown in Fig. 1(a), it is noticed that the first and the third peaks split into two sub-peaks, the splitting

for the first peak is around 6 mT, while the second and fourth peaks remain unitary, this observation is similar to that reported for p-type GaAs [11, 12, 13], n-type InSb [9] and n-type $In_xGa_{1-x}As[8]$ and considered theoretically[19, 20].

QPCs with different shapes $(90^{\circ}, 60^{\circ})$ and 30° QPCs) are used as electron injectors[14, 21, 22]; here the 90° and 60° QPCs inject partially spin polarized electrons while 30° QPC injects unpolarized electron[21, 22]. The unique shape dependence allows us to study the spin texture of the injected 1D electrons and any effects associated with it.

A detailed study of focusing measurement as a function of injector conductance is shown in Fig. 2(a)-(c) for 90° , 60° and 30° angled QPCs, respectively. For the ease of understanding the mechanism we fixed the detector in the middle of the first conductance plateau $G_0 = 2e^2/h$, so that the results are decided by the injection process only. For 90° and 60° QPCs, splitting of the first focusing peak is pronounced when the injector is opened up such that the conductance varies from 0.7G₀ (highlighted by red arrows in Fig. 2) up to the end of the second conductance plateau (2G₀, marked by blue arrows). It is important to emphasize that the splitting of the first focusing peak does not change for the injector conductance up to 2G₀, however, the splitting weakens and disappears as the injector conductance increases slightly above $2G_0[23]$. It may be noted that the asymmetry between the subpeaks is highly sensitive to the injector conductance below $2G_0$. When the QPC becomes sharp (30°) the result changes dramatically, such that the first focusing peak does not show any splitting. This result is in agreement with previous reports[18, 24] where pointed split gates were used for injecting the electrons. We note that the dependence of focusing spectrum on the shape of injector has not been reported previously.

I. Robustness of peak splitting

There is a possibility that the observed splitting of oddnumbered focusing peaks is due to angular spreading of the injected electron (depending on the details of the wavefunction within the QPC) or disorder induced current branching[25]. The electron paths diverging due to these scenarios are not spin related and are maximized if the electrons travel along a quarter circular cyclotron orbit. To rule out such possibilities in our case, we provide further information as below.

First, the experiment was repeated with a linear focusing device fabricated from the same wafer as shown in inset of Fig. 1(b). With a linear geometry two electron paths (due to different injection angle) that are diverging from the injector QPC come back together after travelling in a half circular cyclotron orbit, thus the effect of angular spreading of the injected electron

is minimized. It is seen that the splitting of the first peak and lack of splitting of the second peak in a linear focusing device geometry is similar to that observed with the orthogonal focusing device geometry (Fig. 1). A change of the focusing periodicity compared to the orthogonal focusing geometry is due to the difference in the lithographically defined separation between the injector and detector.

Second, we noticed that the first focusing peak shows a pronounced splitting when the injector conductance is smaller than $2G_0$ $(G_0 = \frac{2e^2}{h})$, however, such splitting is absent at large injector conductance value (e.g. $3G_0$ and $4G_0$) and only a single peak is observed with the orthogonal focusing geometry as shown in Fig. 3(a). It is also important to emphasize that the single peak at large injector conductance value aligns with the dip between the two sub-peaks rather than one of the sub-peaks. Assuming the peak splitting with small injector conductance is due to angular spreading of the injected electron or disorder induced current branching, then with even larger angular spreading at larger injector conductance the splitting should persist (for instance, in Ref.16 the peak splitting is observable even at $6G_0$). However, this expectation contradicts the experimental result and indicates the observed peak splitting is unlikely to arise from electron branching, similarly the lack of an effect due to change of disorder.

Additionally, the intensity of sub-peaks does not necessarily become symmetric at the conductance plateaus if the peak splitting arises from the disorder-induced electron branching as shown in Ref. 16. In our experiment, the peak becomes symmetric at conductance plateaus in all the cases as shown in Fig. 2 and Fig. 3.

Similarly, the smearing out of the peak splitting at higher injector conductance also excludes the possibility that the observed peak splitting is associated with the form of wavefuction. Assuming the peak splitting correlates with the wavefunction, then the increased number of nodes of wavefunction at higher injector conductance may be expected to create more sub-peaks, which clearly disagrees with the experimental result.

Third, an experiment with the quasi-1D channel shifted laterally via an asymmetric gate biasing of the injector and detector was performed. Figure 3(b) and (c) show the result with the quasi-1D channel of the injector shifted laterally by applying an offset of - 0.2 and - 0.4 V, respectively. The asymmetrically biased injector and the symmetrically biased detector were set to a conductance value of G_0 . The peak splitting is not affected by the lateral shift indicating the observation is a disorder-free effect. However, it is noticed that both the sub-peaks shift toward higher magnetic field due to a reduction in the effective separation L between




Figure 4. In-plane magnetic field dependence of focusing peak. (a) Left and right panel are for first and second focusing peaks at different in-plane magnetic fields, Θ is the angle between the magnetic field and the 2DEG plane. Splitting of the first focusing peak is enhanced with decreasing Θ , , i.e. enhanced parallel component. The second peak starts splitting when Θ is 27°. (b) Splitting of first focusing peak (blue-square markers) and second peak (red-circle markers) against in-plane magnetic field. A sharp change in splitting rate of the first focusing peak is seen when $B_{||}$ is around 0.2 T as indicated by the blue arrow.

the injector and the detector. According to Equation (2), a change in L also affects the peak splitting[8]. This observation also highlights one of the limitations of linear focusing geometry where the injector and detector share the central gates. By increasing injector conductance (usually the detector conductance is fixed as is the gate voltage applied to the central gate), it inevitably introduces a lateral shift in the quasi-1D channel. Therefore, a change in peak position and splitting of peaks should be observed in the linear focusing device as well due to the unintentional lateral shift of the quasi-1D channel.

Four, the satellite peaks which differ from the focusing peaks in Fig. 1 are due to scattering centres which disappear after illuminating the device with a red LED at base temperature, however, the split in odd-numbered focusing peaks remains almost unaffected by the illumination, as shown in Fig. 3(d), which shows that the observed effect is disorder-free.

II. In-plane magnetic field dependence

To confirm the split peaks in our experiment are spin related, we performed focusing measurements in a tilted magnetic field. The experiment was performed in a ³He cryostat with rotatable sample holder at a base





Figure 5. Spin polarization of injected electrons. (a) The focusing peaks are reconstructed with two Lorentzian peaks in order to extract peak height accurately. The blue-round markers are raw data for injector conductance at G_0 , the red solid line is the reconstructed peak, the magenta-dashed line and greendotted line are fitting for the two sub-peaks. (b) Extracted spin polarization P as a function of injector conductance, $P = \left| \frac{A_1 - A_2}{A_1 + A_2} \right|$, where A_1 and A_2 are amplitudes of the two sub-peaks obtained from the fitting in plot (a).

temperature of 300 mK. When the angle Θ between the 2DEG plane and magnetic field equals 90°, the field is normal to the 2DEG and when Θ decreases towards 0 an in-plane field component is introduced.

Results shown in Fig. 4(a) correspond to first (left panel) and second focusing peaks (right panel) at different Θ , respectively. The injector conductance is set at $0.8G_0$ at zero in-plane magnetic field. The two sub-peaks of the first focusing peak are pronounced in the whole range studied here with the peak splitting increasing as Θ decreases. It may be noted that as the in-plane component of magnetic field was gradually increased, the split in the first focusing peak was found to increase. Interestingly, the right sub-peak of the first focusing peak shows a disappearance-reappearance behaviour against increasing in-plane field and this behaviour is similar to result in hole gas[13]. The graph on the right panel of Fig. 4(a) shows the effect of inplane magnetic field on the second focusing peak which splits into two when Θ is below 27° (corresponding to a total magnetic field around 0.5 T). It is important to note that the summation of heights of two sub-peaks of the second focusing peak is almost equal to its united counterpart.

Figure. 4(b) shows a plot of splitting of the first and second peaks ΔB_{\perp} against in-plane magnetic field B_{\parallel} . It is noted that the splitting of the first peak experiences a sharp increase from 6.5 mT to around 11.5 mT when the in-plane field is increased up to 200 mT and then gradually rises to 16.3 mT in large in-plane field regime. The splitting of the second focusing peak follows a seemingly linear trend from 10 to 34 mT. The in-plane magnetic field dependence confirms that our observation is spin-related. The non-linear in-plane field dependence of peak splitting (or spin splitting) is an indication of competition



2

3

4 5

10 11 12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

Figure 6. Focusing in k-space in the presence of SOI. The red and white arrows represent the spin-down and spin-up states, respectively. (a) Schematic for the first focusing peak; here the electrons travel along position 1-3. (b) Schematic for the second focusing peak; the electrons travel along position 1-4. The thick black arrow highlights the scattering event at the boundary.

between SOI and the Zeeman splitting[6, 26], and the theory[6] further suggested that the splitting should vary rapidly in the small field regime (where the SOI dominates) and slowly in the large field regime (where the Zeeman splitting dominates), which agrees well with our experimental result. Moreover, the anisotropy of Fermi surface (altering from a sphere to an ellipse in momentum space) in the presence of a large in-plane magnetic field[27, 28] may also contribute to the nonlinear behaviour.

If we estimate the height of the two sub-peaks by reconstructing the first focusing peak with two Lorentzian peaks as shown in Fig. 5(a). asymmetry between the sub-peaks shows that the spin polarization drops to zero at the conductance plateaus and remains finite elsewhere as shown in Fig. 5(b) which agrees with theoretical prediction [21, 22] and is expected when the observed sub-peaks are spin related.

III. Discussion on peak splitting

The splitting of odd-numbered peaks and united single even-numbered peaks[19, 20] together with the nonlinear in-plane field dependence of the peak splitting[6] are indications of the SOI as shown in Fig. 6. The Fermi surface splits into two in the presence of SOI for spin-up and spin-down states, respectively. For the first focusing peak, the injected electrons follow two Fermi surfaces according to their spin orientation, as a consequence the cyclotron radii are different for the two spin states and two focusing peaks are expected. However, the situation changes dramatically for the second focusing peak where a reflection at the boundary is involved. If the incident angle of such reflection is $\sim 0^{\circ}$, which is crucial for the observation of a single second peak, the momentum k changes to -kwhile the spin orientation remains preserved[19, 20]. The swap of momentum together with the preservation of spin orientation will result in hopping between




Figure 7. Conductance of QPCs with different shape. Typical conductance traces of the 90°, 60° and 30° QPC. A dramatic change of the shape in the 0.7 conductance anomaly is observed.

inner and outer Fermi surfaces as shown in Fig. 6(b). The spin-down electrons will initially occupy the inner Fermi surface so that they have smaller cyclotron radius. After the reflection they take the outer Fermi surface which corresponds to a larger cyclotron radius. On the other hand, the spin-up electrons will hop from outer to inner Fermi surface after the reflection. The hopping between the two Fermi surfaces eventually results in the re-union of the two spin states at the detector. If the splitting is due to linear Rashba SOI, the peak splitting ΔB relates to the spin-orbit strength as below[19, 20],

$$\Delta B = \frac{2\sqrt{2}m^*\alpha}{\hbar eL} \tag{2}$$

where m^* is the electron effective mass, α is the Rashba coefficient and it estimated to be 5×10^{-13} eVm in our devices. The estimated Rashba coefficient is considerably larger than the previous report in a GaAs electron gas[10] (and references within Ref. 10). On the other hand, if the splitting is due to k^3 SOI[6], the estimated peak splitting $\sim 23~\mu \text{eV}$ (with $B_{\perp} \sim$ 60 mT) agrees well with theoretical prediction [6] ~ 20 μeV (with $B_{\perp} \sim 50$ mT; see Fig. 1 of Ref. 6). The difference in values might be due to the smaller electron concentration considered in Ref. 6. Since all the devices were fabricated from the same wafer, therefore, in principle all the devices should exhibit the similar SOI (peak splitting). However, the experimental result reveals that the focusing spectrum depends on the shape of the injector.

The shape of the injector primarily affects the spin polarization which is manifested as a change in the shape of the 0.7 conductance anomaly [21, 22, 29] as shown in Fig. 7. Conductance plateaus are well defined for 90°, 60° and 30° QPC. A pronounced additional feature occurs around $0.5G_0$ in the 90° QPC, a rather faint 0.7 structure is observed in the 60° QPC, and no feature other than the integer conductance plateaus is present in the 30° QPC. It is predicted [29] that in a longer QPC the interaction effect introduce a larger

intrinsic spin polarization, so that the 0.7 conductance anomaly tends to appear at $0.5G_0$. On the other hand, spin polarization generated by a short QPC is negligible and the 0.7 anomaly smears out. In the studied devices, the lithographic defined channel length remains the same, tuning the angle of QPCs dramatically affects the effective length where electrons can strongly interact, which leads to a change in the shape of the 0.7 anomaly.

It appears that the extent to which the 1D electrons are polarized alters the magnitude of the 2D SOI. A detectable SOI (observable via the peak splitting) is triggered with injected partially spin polarized electrons while a small SOI (lack of peak splitting) is obtained with unpolarized injection, indicating the possibility of modulating the SOI in the 2DEG via injection of the different spin species. A recent theoretical work suggested the connection between the 1D wire and 2D reservior can affect the experession of the SOI[30]. It is an open question as how this modulation occurs in a heterostructure, though we speculate the dynamic nuclear polarization which is directly proportional to spin polarization of the injected electrons[31] might be a possible mechanism.

Conclusion

In conclusion, we have demonstrated that interaction between electrons in quasi-1D channels leads to a finite spin polarization which in turn modulates the spin-orbit interaction. It is found that the spinorbit interaction can be enhanced by injecting a spin polarized current into the 2DEG. The results provide new information on the zero-field splitting and correlation with related phenomena such as the spin Hall effect and magnetic injection. The evidence on engineering the spin orbit interaction in GaAs electron gas is a step towards realizing high quality spinbased systems which can selectively control the spin polarization and SOI. The results will stimulate further research work into the emerging areas of quantum technologies and spintronics which are closely linked to each other.

Acknowledgments

The work is funded by the Engineering and Physical Sciences Research Council (EPSRC, UK).

References

[1] Kato Y., Myers R., Gossard A. and Awschalom D. 2004 science **306** 1910–1913

- [2] Wunderlich J., Park B., Irvine A. C., Zarbo, L. P. and Rozkotova E., Nemec P., Novak V., Sinova, J. and Jungwirth T. 2010 science 330 1801–1804
- [3] Stein D., Klitzing K. v. and Weimann G. 1983 Phys. Rev. Lett. 51 130–133
- [4] Jusserand B., Richards D., Peric H. and Etienne B. 1992 Phys. Rev. Lett. 69 848–851
- [5] Ramvall P., Kowalski B. and Omling P. 1997 Phys. Rev. B 55 7160-7164
- [6] Lommer G., Malcher F. and Rossler U. 1988 Phys. Rev. Lett. 60 728-731
- [7] Chuang P. and Ho S. C., Smith L. W., Sfigakis F., Pepper M., Chen C. H., Fan J. C., Griffiths J. P., Farrer I., Beere H. E., Jones G. A. C., Ritchie D. A. and Chen T. M. 2015 Nature nanotechnology 10 35–39
- [8] Lo S. T., Chen C. H., Fan J. C., Smith L. W., Creeth G. L., Chang C. W., Pepper M., Griffiths J. P., Farrer I., Beere H. E., Jones G. A. C., Ritchie D. A. and Chen T. M. 2017 Nature Communications 8 15997
- [9] Dedigama A. R., Deen D., Murphy S. Q., Goel N., Keay J. C., Santos M. B., Suzuki K., Miyashita S. and Hirayama Y. 2006 Physica E: Low-dimensional Systems and Nanostructures 34 647-650
- [10] Studer M., Salis G., Ensslin K., Driscoll D. C. and Gossard A. C. 2009 Phys. Rev. Lett. 103 027201
- [11] Rokhinson L. P., Larkina V., Lyanda-Geller Y. B., Pfeiffer L. N. and West K. W. 2004 Phys. Rev. Lett. 93 146601
- [12] Rokhinson L. P., Pfeiffer L. N., and West K. W. 2006 Phys. Rev. Lett. 96 156602
- [13] Chesi S., Giuliani G. F., Rokhinson L. P., Pfeiffer L. N. and West K. W. Phys. Rev. Lett. 106 236601
- [14] Yan C., Kumar S., Thomas K., Pepper M., See P., Farrer I., Ritchie D., Griffiths J. P. and Jones G. A. C. 2017 Phys. Rev. Applied 8 024009
- [15] Yan C., Kumar S., Pepper M., See P., Farrer I., Ritchie D., Griffiths J. P. and Jones G. A. C. 2017 Nanoscale Research Letters 12 553
- [16] Ohno Y., Young D. K., Beschoten B., Matsukura F., Ohno H. and Awschalom D. D. 1999 Nature 402 790
- [17] Bhat S. G. and Kumar P. A. 2014 Scientific reports 4 5588
- [18] van Houten H., Beenakker C. W. J., Williamson J. G., Broekaart M. E. I., van Loosdrecht P. H. M., van Wees B. J., Mooij J. E., Foxon C. T. and Harris J. J. 1989 Phys. Rev. B 39 8556-8575
- [19] Usaj G. and Balseiro C. A. 2004 Phys. Rev. B 70 041301
- [20] Reynoso A., Usaj G. and Balseiro C. A. 2007 Phys. Rev. B 75 085321
- [21] Wang C. K. and Berggren K. F. 1996 Phys. Rev. B 54 R14257
- [22] Wang C. K. and Berggren K. F. 1998 Phys. Rev. B 57 4552
- [23] Li J., Gilbertson A. M., Litvinenko K. L., Cohen L. F. and Clowes S. K. 2012 Phys. Rev. B 85 045431
- [24] Potok R. M., Folk J. A., Marcus C. M. and Umansky V. 2002 Phys. Rev. Lett. 89 266602
- [25] Maryenko D., Ospald F., Klitzing K. v., Smet J. H., Metzger J. J., Fleischmann R., Geisel T. and Umansky V. 2012 Phys. Rev. B 85 195329
- [26] Bladwell S. and Sushkov O. P. 2015 Phys. Rev. B 92 235416
- [27] Ohtsuka K., Takaoka S., Oto K., Murase K. and Gamo K.
 1998 Physica B: Condensed Matter 249251 780 783
- [28] Kamburov D., Mueed, M. A., Shayegan M., Pfeiffer L. N., West K. W., Baldwin K. W., Lee J. J. D. and Winkler R. 2013 Phys. Rev. B 88 125435
- [29] Jaksch P., Yakimenko I. and Berggren K.-F. 2006 Phys. Rev. B **74** 235320
- [30] Rainis D. and Loss D. 2014 Phys. Rev. B 90 235415
- [31] Kawamura M., Ono K., Stano P., Kono K. and Aono T. 2015 Phys. Rev. Lett. 115 036601