



FEATURES

- 48 track verification channels
- SIRF-IV low power chipset
- Tracking sensitivity -163dBm
- Acquisition sensitivity -147dBm
- Cold start < 34 seconds
- Hot start < 1sec under open sky
- 2.5m CEP accuracy
- Support SAGPS function
- SBAS (WAAS, EGNOS) support
- 2M Bytes flash memory for data logging, with 16M-Bit binary data per record that stores up to 256K data records
- Log data can be exported to mapping software such as Google Earth and TrackMaker
- Logging data interval programmable: by time or distance
- USB version 1.1/2.0 interface
- Easy-plug-in Notebook
- Easy-installation USB driver
- Super mini size: 73.5x27x10 mm

GT-730F(L) Data Logger Dongle Fast Acquisition high-Sensitivity 48 track verification USB GPS Dongle

The GT-730F(L) is a single board of USB-GPS receiver for customers who require easy system integration and minimal development risk.

The GT-730F(L) is optimized for good performance and low cost. Its 48 parallel channels and SiRF-IV search bins provide short start-up time and fast signal acquisition. Having fast time-to-first-fix and high sensitivity, the GT-730FL-S offers good navigation performance even in urban canyons.

The GT-730F(L) is capable of keeping up to 256K records or positions, including longitude, latitude, speed, UTC, and tag data. The location histories can be exported to mapping software such as Google Earth or TrackMaker.

Satellite-based augmentation systems, such as WAAS and EGNOS, are supported to yield improved accuracy. Besides it also supports SAGPS function and fixed in the short time.

The onboard patch antenna provides good signal reception. It provides fast satellite signal acquisition and short startup time. Acquisition sensitivity of -147dBm and tracking sensitivity of -163dBm offers good navigation performance even in urban canyons having limited sky view.

USB interface are provided on the interface connector. Supply voltage of 5V is supported.

TECHNICAL SPECIFICATIONS

Receiver Type	48 parallel channels, L1 C/A code
Accuracy	Position 2.5m CEP Velocity 0.1m/sec
Startup Time (average)	< 1sec hot start < 34sec cold start
Signal Reacquisition	1s
Sensitivity	-147dBm acquisition -163dBm tracking
Update Rate	1Hz standard (5Hz/10Hz special order)
Dynamics	4G (39.2m/sec ²)
Serial Interface	USB
Protocol	NMEA-0183 V3.01 GPGGA, GPGLL, GPGSA, GPGSV, GPRMC, GPVTG, GPZDA 4800/9600/19200/38400 baud, 8, N, 1
Datum	Default WGS-84 User definable
Input Voltage	5V DC
Power Consumption	< 30mA (1Hz standard version)
Dimension	73.5mm L x 27mm W x 10mm H
Weight:	18g (Including Battery)
Operating Temperature	-40°C ~ +85°C
Humidity	5% ~ 95%

Binary Messages

See *Binary Message Protocol User's Guide* for detailed descriptions.

CanMore Electronics Co., LTD.

No. 40, Chenggong 5th St., Jhubei City, Hsinchu County, 302, Taiwan

Phone +886 3 6586046

Fax +886 3 6583940

Email sales@canmore.com.tw

Website: [http:// www.canmore.com.tw](http://www.canmore.com.tw)

<http://canmorecorp.trustpass.alibaba.com/>

© 2000 CanMore Electronics Co., Ltd. All rights reserved.

Not to be reproduced in whole or part for any purpose without written permission of CanMore Electronics Co., Ltd. ("CMEC")

Information provided by CMEC is believed to be accurate and reliable. These materials are provided by CMEC as a service to its customers and may be used for informational purposes only. CMEC assumes no responsibility for errors or omissions in these materials, nor for its use. CMEC reserves the right to change specification at any time without notice.

These materials are provides "as is" without warranty of any kind, either expressed or implied, relating to sale and/or use of CMEC products including liability or warranties relating to fitness for a particular purpose, consequential or incidental damages, merchantability, or infringement of any patent, copyright or other intellectual property right. CMEC further does not warrant the accuracy or completeness of the information, text, graphics or other items contained within these materials. CMEC shall not be liable for any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of these materials.

CMEC products are not intended for use in medical, life-support devices, or applications involving potential risk of death, personal injury, or severe property damage in case of failure of the product.