

Regional Construction Standards Third Edition

Chesapeake modifications to Regional Standards Third Edition

1. The width of select bedding stone will be based on the inside pipe diameter plus (2) feet. The depth required will be six (6) inches for pipes less than forty-eight (48) inches and 0ne (1) foot for larger pipe sizes or as determined by the Engineer. (PFM Volume III \ Division 16 - Bidding Material (Drainage and Utility Pipe))

HRPDC Regional Construction Standards

Amendment No. 1

This Amendment modifies, revises, and /or updates the Third Edition dated January 2003.

1. Change Depth (FT)-Dimension (W) Table as follows ,and change the second note below the table to read " ... GREATER of the two dimensions listed, or O.D. + 2E " instead of "....LESSER of the two dimensions listed":

Depth (FT.)	Dimension "W"*		
0 - 4	2.5' OR O.D. + 2E		
4 - 10	3.0' OR O.D. + 2E		
10 - 14	4.0' OR O.D. + 2E		
14 - 20	5.0' OR O.D. + 2E		
OVER 20	Special DESIGN - SEE		
	CONTRACT		
	DOCUMENTS		

Sheet 1of 2

Chesapeake		TRENCH WIDTH DETAIL FOR PAVEMENT OF CONTINGENT ITEMS		
		DR. BY:	DATE:	
08/15/03	REV. FOR INTERNET 2003	CHK. BY:	DATE	EW 03
DATE	REVISIONS	APP. BY:	DATE	₀₄
	EU E GO NAC	ADELL COLDENSIO	CC 2md Edition	(01)EARTH\/DRKS/E\/\\\(0.4\E\/\\0.02\\(1.12\)