

4-in-1 Big Boss Lanyard

GUARDIAN
FALL PROTECTION

Part #	Length	Description
11520	6'	w/18" D-ring Extension, & Tie-Back Leg.
11521	6'	w/Bungee Leg, Rebar Hook, & Tie-Back Leg. No D-ring extension.
11522	6'	w/18" D-ring Extension & (2) Tie-Back Legs.

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.13-2013, and ANSI A10.32-2012 regulations.

Custom configurations available. Not repairable. Contact customer service for details.

4-in-1 Big Boss Lanyard is suitable for the following applications:



Personal Fall Arrest: 4-in-1 Big Boss Lanyard may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is up to 12' for workers from 130-310 lbs., and up to 6' for workers from 311-420 lbs. Applicable D-ring: Dorsal.



Restraint: 4-in-1 Big Boss Lanyard may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.

Materials: nylon, polyester, and galvanized steel.

Attach 4-in-1 Big Boss Shock Absorber to compatible harness D-ring, OR attach Extension Lanyard Leg to compatible harness D-ring with compatible connector.

Attach 4-in-1 Big Boss Standard 6' Leg to compatible anchorage connector, OR attach Tie-Back Leg around compatible structural anchor. If using lanyard with rebar hook end, rebar hook must NEVER be attached to harness D-ring, and must ONLY be attached to compatible structural anchor.

NEVER work with both Standard 6' Leg and Tie-Back Leg connected; attach unused leg to compatible harness lanyard keeper. ALWAYS maintain 100% tie-off.

MAXIMUM 1 user per 4-in-1 Big Boss Lanyard.

UPC-A Codes: 11520: 672421115207; 11521: 672421115214; 11522: 672421115221.

