aselsan

Node.JS Appliances on Embedded Linux Devices

Mehmet Fatih Karagöz & Cevahir Turgut

Outline

- Introduction to Node.js
- Cross-compiling Node.js and Node Package Manager(NPM)
- Development environment
- Scripting samples in embedded devices
- Development story of a surveillance application
- Demo
- Questions

Outline

- Introduction to Node.js
- Cross-compiling Node.js and NPM
- Development environment
- Scripting samples in embedded devices
- Development story of a surveillance application
- Demo
- Questions

- What is Node.js?
 - Node.js is a platform built on Chrome's JavaScript runtime (V8) for easily building fast, scalable network applications.
- Event-Driven
- Non-Blocking I/O
- Lightweight
- Efficient HW Usage

Advantages

- Open source
- HW Efficiency
- Learning Curve
- Development Time
- Javascript / No Compile
- NPM Package Manager

Disadvantages

- Small Developer Pool
- Bad at CPU Bound Jobs
- Asynchronous Debugging



- What is learning curve?
 - Node.JS uses Javascript
 - Most web developers are familiar with the language
 - You can get started with building very basic application in less than one hour (that includes installation time!)

- NPM (Node Packaged Modules)
- NodeJS package management system
- Install modules very easily even on embedded
 - "npm install express"
- Installs dependant modules too
- Global install option
 - "npm install -g express"

Popular Modules

- Express
- Request
- Async
- ▶ Grunt
- socket.io
- Mocha
- Underscore
- Mongoose
- Redis
- Connect



Outline

- Introduction to Node.js
- Cross-compiling Node.js and NPM
- Development environment
- Scripting samples in embedded devices
- Development story of a surveillance application
- Demo
- Questions

Cross-compiling Node.js and NPM

Where is Node.js?

Download

- http://nodejs.org/download
- ▶ Git
 - git clone git://github.com/joyent/node.git
 - cd node
 - git checkout v0.10
- Node.js is released under the MIT license.

Cross-compiling Node.js and NPM

Configuration Options

- Usage: configure [options]
- Options:
 - --without-npm Don't install the bundled npm package manager
 - --without-ssl Build without SSL
 - --without-snapshot Build without snapshotting V8 libraries. You might want to set this for cross-compiling.
 - --dest-cpu=DEST_CPU CPU architecture to build for. Valid values are: arm, ia32, x64
 - --dest-os=DEST_OS Operating system to build for. Valid values are:
 win, mac, solaris, freebsd, openbsd, linux, android



Cross-compiling Node.js and NPM

How to make and install

- export AR=arm-linux-gnueabihf-ar
- export CC=arm-linux-gnueabihf-gcc
- export CXX=arm-linux-gnueabihf-g++
- export LINK=arm-linux-gnueabihf-g++
- ./configure --without-snapshot --dest-cpu=arm --dest-os=linux
- make
- make install DESTDIR=~/node-armhf/

Outline

- Introduction to Node.js
- Cross-compiling Node.js and NPM
- Development environment
- Scripting samples in embedded devices
- Development story of a surveillance application
- Demo
- Questions



Development Environment

Suitable Editors

- Vim
- Gedit
- Webstorm
- Eclipse / Nodeclipse Plugin
- Cloud9 (Cloud based editor)

Development Environment

- "node debug myscript.js"
- Debugging Options
 - cont, c Continue execution
 - next, n Step next
 - step, s Step in
 - out, o Step out
 - pause Pause running code (like pause button in Developer Tools)
 - setBreakpoint(), sb() Set breakpoint on current line
 - setBreakpoint(line), sb(line) Set breakpoint on specific line
 - setBreakpoint('fn()'), sb(...) Set breakpoint on a first statement in functions body
 - setBreakpoint('script.js', I), sb(...) Set breakpoint on first line of script.js
 - clearBreakpoint, cb(...) Clear breakpoint
 - backtrace, bt Print backtrace of current execution frame
 - list(5) List scripts source code with 5 line context (5 lines before and after)
 - watch(expr) Add expression to watch list
 - unwatch(expr) Remove expression from watch list
 - watchers List all watchers and their values (automatically listed on each breakpoint)
 - repl Open debugger's repl for evaluation in debugging script's context



Outline

- Introduction to Node.js
- Cross-compiling Node.js and NPM
- Development environment
- Scripting samples in embedded devices
- Development story of a surveillance application
- Demo
- Questions

GPIO/LED on/off

var exec = require('child_process').exec;

```
/* EXEC SYSTEM CALL */
var setLedOn = function() {
   exec('echo 1 > /sys/class/leds/d440\:red/brightness', function() {
      console.log('Led is on!');
   });
}
```

CPU / Memory Usage

```
var os = require('os');
```

```
/* CPU USAGE */
var printCPULoad = function() {
  var load = os.loadavg();
  var message = "1 Min: %" + Math.floor(load[0]*100) + " 5 Min: %" + Math.floor(
  load[1]*100) + " 15 Min: %" + Math.floor(load[2]*100);
  console.log(message);
}
```

```
/* MEMORY USAGE */
var printMemLoad = function() {
  var freemem = os.freemem();
  var totalmem = os.totalmem();
  var message = "Free Mem: " + Math.floor(freemem/1000000000) + " Total Mem: " +
  Math.floor(totalmem/1000000000);
  console.log(message);
}
```

▶ Timers

```
/* TIMER EXAMPLE */
var val = 0;
var setLed = function(){
   var cmd = "echo " + val + " > /sys/class/leds/d440\:red/brightness";
   console.log(cmd);
   exec(cmd , function(){
        if(val === 0)
            val = 1;
        else
            val = 0;
        console.log('value: '+ val);
   });
}
setInterval(setLed, 1000);
```

Ini Parser

```
/* INI PARSER using node-iniparser module */
var iniparser = require('iniparser');
iniparser.parse('./config.ini', function(err,data){
    var version = data.version;
});
```

```
config.ini:
```

```
;sample config ini file
name = Iniparser Demo
version = 0.1
```

"npm install iniparser"

Outline

- Introduction to Node.js
- Cross-compiling Node.js and NPM
- Development environment
- Scripting samples in embedded devices
- Development story of a surveillance application
- Demo
- Questions

Main Purpose


- Demonstrate usage scenario of Node.js in real world app
- Give more information about network classes of Node.js
- Run complete Node.js app in embedded platform

Example Surveillance System

- Smart IP Cameras
 - ▶ to detect motion, etc.
- Server PC
 - at Command Control Center
 - monitoring cameras, their alarms, etc.



Deployment Model of Example System




Used Components


- ▶ IGEPv2 Boards
 - ▶ DM3730 Texas Instruments processor
 - ARM Cortex A8 IGHz
 - Camera ISP
 - ▶ 512 Megabytes RAM / 512 Megabytes FLASH
 - ▶ Ethernet 10/100 MB BaseT
 - And more (C64+ DSP 800MHz, 3D Accelerator SGX530 @ 200 MHz, ...)
- Kernel
 - **2.6.37**
- Compiler:
 - GCC version 4.6.3



Component Diagram




Component Diagram (with messages)





Deployment Model of Example System





Development Story of a Surveillance Application - Video App

Video App

- Fake Application to simulate motion detection
- Written using Boost CPP Libraries
- Connected to Camera System App with TCP
- Produces periodic alarm messages
- Receives configuration messages



Development Story of a Surveillance Application - Video App

```
t.async wait( boost::bind(periodicTimer, boost::asio::placeholders::error, &t) );
boost::thread thread1(boost::bind(&boost::asio::io service::run, &io));
while (1) {
    read length = boost::asio::read((socket ), boost::asio::buffer((char*) &(buffer[0]), (size t) 2),
            boost::asio::transfer at least(2), ec);
    if (!ec && read length == 2) {
        cout << "** VideoAppMain: configuration message is received" << endl;
        opcode = buffer[0];
        data = buffer[1];
        switch (opcode) {
        case OPCODE VIDEO SRC CHG:
        case OPCODE MD MODE CHG:
            if (data == MD MODE OFF) {
                                          cout << "** VideoAppMain: MD Mode: OFF ** " << endl;
                md mode = MD MODE OFF;
            } else if (data == MD MODE 1) {
                md mode = MD MODE 1;
                                        cout << "** VideoAppMain: MD Mode: 1 ** " << endl;
                alarm period = 10;
            } else if (data == MD MODE 2) {
                md mode = MD MODE 2;
                                        cout << "** VideoAppMain: MD Mode: 2 ** " << endl;
                alarm period = 30;
            buffer[0] = OPCODE MD MODE CHG;
            buffer[1] = (char) md mode;
            write length = boost::asio::write((socket ),
                    boost::asio::buffer(buffer, 2),
                    boost::asio::transfer all(), ec);
```

Development Story of a Surveillance Application - Camera SystemMgr App

- Camera SystemMgr App
 - Written using Node.js
 - Manages other software elements running on camera through IPC
 - Store configurations
 - Connection interface of camera to server
 - Includes 2 TCP servers and 1 UDP client
 - ▶ I TCP Server for IPC with VideoApp
 - I TCP Server
 - □ to get configuration messages from Server
 - □ to send alarm messages to Server
 - ▶ I UDP broadcaster to send heartbeat



Camera SystemMgr App

```
/* VIDEO APP TCP SERVER STARTS: TCP Connection between Video App and Camera System App (IPC) */
var net = require('net');
var video = {video src: 1, md mode: 0, socket: null};
var video app server = net.createServer(function (socket) {    //'connection' listener
  console.log('Video app connected');
    socket.on('data', function(data){    //Emitted when data is received
   if (data.length === 2) {
        if (data[0] === VIDEO SRC OPCODE) { //ACK taken from VideoApp
            console.log('Video source message received! Source: ' + data[1]);
           video.video src = data[1];  //Save state
        else if(data[0] === VIDEO MODE OPCODE){
        console.log('Alarm message received!');
           if(device.tcp socket != null){
               sendAlarm(device.tcp socket, data[1]); //Send alarm to Server
        else{
  });
  socket.on('close', function(){    //Emitted once the socket is fully closed
        video.socket = null;
  });
  video.socket = socket;
));l
video app server.listen(1337, '127.0.0.1');
console.log('Video app server listening to 127.0.0.1:1337');
 /* VIDEO APP TCP SERVER ENDS */
```

Camera SystemMgr App

```
/* SYSTEM TCP SERVER STARTS: TCP Connection between Camera System App and Server */
function setVideoSrc(socket, src){
     var msg = new Buffer([VIDEO SRC OPCODE, src]);
     socket.write(msg);
function setMdMode(socket, mode){
     var msg = new Buffer([VIDEO MODE OPCODE, mode]);
     socket.write(msq);
war system server = net.createServer(function (socket) {
   console.log('Server app connected');
   socket.on('data', function(data){
     if(data.length === 3 && data[0] === device.id){
         console.log('Conf Received!');
         if(video.socket != null){
             setVideoSrc(video.socket, data[1]); //Send configuration to VideoApp
              setMdMode(video.socket, data[2]);
   ));
   socket.on('close', function(){
         device.tcp socket = null;
   ));
   device.tcp socket = socket;
 3);
 system server.listen(1338);
 console.log('System server listening to port 1338');
```

Camera SystemMgr App

```
/* UDP HEARTBEAT SENDER: UDP Broadcaster */
 var dgram = require('dgram');
 var client = dgram.createSocket("udp4");
client.setBroadcast(true); //enable broadcasting after socket binding
٠((
setInterval(function(){
     var msg = {device id: device.id,
                 status: 'OK',
                 location: {lat: 100, lon: 100},
                vid src: video.video src,
                md mode: video.md mode,
                time: Date.now());
     var message = new Buffer (JSON.stringify(msg)); //Convert a value/an object to JSON
     client.send(message, 0, message.length, 1400, "255.255.255.255", function(err, bytes) {
       console.log('heartbeat sent!');
     });
 }, 2000);
 /* UDP HEARTBEAT ENDS */
```

- Connection with online cameras
 - Camera discovery by listening Broadcast/UDP heartbeat messages
 - Connecting TCP port of cameras
- Configuring cameras
- Collects alarms from cameras
- Serve all information to web interface
 - Static Content Serving
 - Express and Socket.io modules of Node.js
- Handles user inputs from web interface
 - Management of all cameras
- Handling multi-client/multi-camera systems



```
udp server.on("message", function (msg, rinfo) { //rinfo Object. Remote address information
   var device info = JSON.parse(msg);
   for(var i = 0; i < devices.length; i++){</pre>
       if (devices[i].device id === device info.device id) ( //if device is found, update and notify WEB clients
   if(i === devices.length){
                                                        //no device is found; add to list
       devices[i] = {};
                                                        devices[i].status = device info.status;
       devices[i].device id = device info.device id;
       devices[i].location = device info.location;
                                                        devices[i].vid src = device info.vid src;
       devices[i].md mode = device info.md mode;
                                                        devices[i].time = device info.time;
       devices[i].ip = rinfo.address;
       /* TCP CLIENT */
       devices[i].client = new net.Socket(); //create socket (TCP client) to connect new device
       devices[i].client.connect(PORT, devices[i].ip, function() {
           console.log('CONNECTED TO: ' + devices[i].ip + ':' + PORT);
           sendNewCamBySocket(devices[i]);
       });
       devices[i].client.on('data', function(data) {      // Add a 'data' event handler for the client socket
           var alarm data = JSON.parse(data);
           console.log('Alarm from ' + alarm data.camera id);
           sendAlarmBySocket(alarm data);
       });
       sendDropCamBySocket(devices[i].device id);
           devices.splice(i,1);
           console.log('Connection closed');
       });
       devices[i].client.on('error', function() { // Add a 'error' event handler for the client socket
```

```
/* WEBSERVER */
var express = require('express');
 var app = express();
 var webserver = require('http').createServer(app);
 var io = require('socket.io').listen(webserver);
io.configure(function(){
   io.enable('browser client etag');
   io.set('log level', 1);
   io.set('transports', [
     'flashsocket',
     'htmlfile',
   1);
 3);
= app.configure(function(){
   app.use(express.static( dirname + '/static/app'));
٠; ( { '
 webserver.listen(3000);
 console.log("Webserver listening 3000");
```

```
/* WEBSOCKET */
 var websockets = [];
io.sockets.on('connection', function (socket) {
   console.log('Client Connected!!!');
   socket.on('getDeviceList', function (data) {
     sendDeviceList(socket);
   });
   socket.on('config', function (data) {
     var device = findDevice(devices, data.device id);
     sendDeviceConf(device.client, device.device id, data.vid src, data.md mode);
   3);
   websockets.push(socket);
 -});
If unction sendDeviceList(socket){
   if (devices.length > 0) {
     for(var i=0; i<devices.length; i++){</pre>
         socket.emit('caminfo', {device id: devices[i].device id, status: devices[i].status,
                                  location: devices[i].location, vid src: devices[i].vid src,
                                  md mode: devices[i].md mode, time: devices[i].time, ip:devices[i].ip});
function sendAlarmBySocket(alarm data){
     if(websockets.length > 0){
         for(var i=0; i<websockets.length; i++) {</pre>
              websockets[i].emit('alarm', {alarm: alarm data});
```

```
If tunction sendNewCamBySocket(device){
     if (websockets.length > 0) {
         for (var i=0; i<websockets.length; i++) {</pre>
              websockets[i].emit('newcam', {device id: device.device id, status: device.status,
                                             location: device.location, vid src: device.vid src,
                                             md mode: device.md mode, time: device.time, ip:device.ip});
Function updateCamBySocket(device){
     if(websockets.length > 0){
         for(var i=0; i<websockets.length; i++){</pre>
              websockets[i].emit('updatecam', {device id: device.device id, status: device.status,
                                                location: device.location, vid src: device.vid src,
                                                md mode: device.md mode, time: device.time, ip:device.ip});
function sendDropCamBySocket(device id){
     if (websockets.length > 0) {
         for(var i=0; i<websockets.length; i++) {</pre>
              websockets[i].emit('dropcam', {device id: device id});
```

Development Story of a Surveillance Application - Web Interface

Web Interface

- ► HTML5/Javascript
- Web Sockets
 - Socket.io
- Angular.js
- Ajax Based
 - No need to refresh
- Browser Compatibility
 - ▶ IE9, Firefox, Chrome tested

Web Interface WebSocket Code Samples

From "http://socket.io/#how-to-use"

```
SERVER (APP.JS)
                                                        CLIENT (INDEX.HTML)
                                                          <script src="/socket.io/socket.io.js"></script>
  var app = require('express').createServer()
    , io = require('socket.io').listen(app);
                                                          <script>
                                                            var socket = io.connect('http://localhost');
                                                            socket.on('news', function (data) {
  app.listen(80);
                                                              console.log(data);
                                                              socket.emit('my other event', { my: 'data' });
  app.get('/', function (req, res) {
    res.sendfile( dirname + '/index.html');
                                                            });
  });
                                                          </script>
  io.sockets.on('connection', function (socket) {
    socket.emit('news', { hello: 'world' });
   socket.on('my other event', function (data) {
      console.log(data);
    1);
  1);
```

Web Interface WebSocket Code Samples

```
angular.module('myApp.controllers', []).
 controller('MyCtrl1', ['socket', '$scope', function(socket, $scope) {
    $scope.devices = [];
   $scope.alarms = [];
    $scope.setMdMode = function(device, md val){
        var msg = {device id: device.device id, vid src: device.vid src, md mode: md val};
       socket.emit('config', msg);
    $scope.setVidSrc = function(device, src val){
        var msg = {device id: device.device id, vid src: src val, md mode: device.md mode};
        socket.emit('config', msg);
    };
    socket.emit('getDeviceList', {data: 'abc'});
    socket.on('caminfo', function (data) { //when socket is connected
        $scope.devices.push(data);
    });
```

Web Interface WebSocket Code Samples

```
socket.on('newcam', function (data) { //new camera is found after socket connectio
 socket.on('updatecam', function (data) {
     for(var i=0; i<$scope.devices.length; i++){</pre>
          if($scope.devices[i].device id === data.device id){
              $scope.devices[i].time = data.time;
              $scope.devices[i].vid src = data.vid src;
              $scope.devices[i].md mode = data.md mode;
              $scope.devices[i].status = data.status;
              break:
 });
 socket.on('dropcam', function (data) {
      for(var i=0; i<$scope.devices.length; i++){</pre>
          if($scope.devices[i].device id === data.device id){
              $scope.devices.splice(i,1);
              break;
 });
 socket.on('alarm', function (data) {
      console.log(data.alarm);
      $scope.alarms.push(data.alarm);
 ));
31)
.controller('MyCtr12', [function() {
)]);
```

Outline

- Introduction to Node.js
- Cross-compiling Node.js and NPM
- Development environment
- Scripting samples in embedded devices
- Development story of a surveillance application
- Demo
- Questions

Questions

- Demo Codes
 - github.com/mfkaragoz/elce2013demo
- Thank You!
 - Mehmet Fatih KARAGOZ mfatihkaragoz@yahoo.com
 - Cevahir TURGUT cevahir.turgut@gmail.com