



# WiFi 6 Gateway for Service Providers

AVDSL WAN Port | Gigabit Ethernet WAN Port | WiFi 6 | TR-069

## VR-3071

The VR-3071 is Comtrend's first WiFi 6 Gateway to give end users an optimized WiFi experience. Comtrend purpose-built the VR-3071 for enhanced whole-home coverage using the latest in Wireless technology.



### **Increased Efficiency and Optimized Coverage**

WiFi 6 is the latest in WiFi technology utilizing OFDMA, MU-MIMO, 1024-QAM and more for an enhanced WiFi experience.



### **Use More Devices Simultaneously**

WiFi 6 is ideal for simultaneously running multiple high-bandwidth devices.



### **Multi-WAN for Deployment Flexibility**

The VR-3071 is equipped with both a Gigabit Ethernet WAN and a DSL WAN for multiple deployment options with one product.



### **Remote Management for Reduced Truck Rolls**

The VR-3071 supports TR-069 to easily setup, manage, troubleshoot and control the CPE remotely.



COMTREND

530 Technology Drive Ste 100

Irvine, CA 92618

(949) 753-9640 | [us.comtrend.com](http://us.comtrend.com)

DS\_VR-3071\_V1.0.1

## Specifications



### Hardware

- RJ-11 X 1 for ADSL2+/VDSL2
- RJ-45 X 4 for LAN (10/100/1000 Base-T auto-sense)
- RJ-45 X 1 for WAN (10/100/1000 Base-T auto-sense)
- Reset button X 1
- WPS & WiFi On/Off button X 2
- WiFi Antennas X 4 (2 dual band antenna & 2 single band antenna)
- Power switch X 1
- USB 3.0 Host X 1

### VDSL

- Supports VDSL profiles, 8a/b/c/d, 12a/b, 17a, 30a, and 35b
- Seamless Rate Adaption (SRA)
- G.vector and G.vector friendly mode (G.993.2 Annex Y)
- US0 band support
- PhyR and G.INP support

### ADSL

- T1.413, G.992.1 (G.dmt), G.992.2 (G.lite), G.992.3 (ADSL2) and G.992.5 (ADSL2+)
- Annexes A, L (Reach Extended ADSL2), and M (Enhanced Upstream Speed)
- Seamless Rate Adaption (SRA)
- Support VC-based and LLC-based multiplexing
- Support up to 16 PVCs
- ATM shaping: UBR/CBR/VBR-rt/VBR-nrt
- PhyR and G.INP support

### WLAN

- AX5400Mbps PHY Rate
- 1W Ultra High TX Power
- IEEE 802.11ax, 2.4GHz, 2T2R, backward compatible with 802.11n/g/b
- IEEE 802.11ax, 5GHz, 4T4R, backward compatible with 802.11ac/n/a
- WPA/WPA2/WPA3-PSK with TKIP & AES security type
- Multiple SSID
- MAC address filtering
- 802.1x radius supported
- Supports entire 5GHz band including Dynamic Frequency Selection (DFS) channels
- Supports band steering
- Supports beamforming

### LAN

- 10/100/1000 Base T, IEEE 802.3, IEEE 802.3u IEEE 802.3abSupport MDI/MDIX

### Management

- TR-069/TR-181/TR-104/TR-111, SNMP, Telnet, Web-based management, Configuration backup and restoration
- Fine Point's TR-069 enhanced functionality is available on this model with a firmware upgrade
- Software upgrade via HTTP, TFTP server, or FTP server

### Networking Protocols

- RFC 1483/2684 VC-MUX, LLC/SMAP encapsulations for bridged or routed packet
- IPoE, PPPoE, Bridge, IPoA, PPPoA
- PPPoE pass-through, Multiple PPPoE sessions on single WAN interface
- PPPoE Filtering of non-PPPoE packets between WAN and LAN
- Transparent bridging between all LAN and WAN interfaces
- 802.1p/802.1q VLAN Support
- Spanning Tree Algorithm
- IGMP Proxy V1/V2/V3, IGMP Snooping V1/V2/V3, Fast leave
- Static route, RIP v1/v2, ARP, RARP, SNTP
- DHCP Server/Client/Relay
- DNS Proxy/Relay, Dynamic DNS
- Internet Printing Protocol
- UPnP
- IPv6 subset

### Firewall/Filtering

- Stateful Packet Inspection Firewall
- Stateless Packet Filter
- Parental Control
- URI/URL Filtering
- Denial of Service (DOS): ARP attacks, Ping attacks, Ping of Death, LAND, SYNC, Smurf, Unreachable, Teardrop
- Port Scan Detection and Protection
- TCP/IP/Port/interface filtering rules Support both incoming and outgoing filtering

### NAT/PAT

- Supports One to One, Many to One, Many to Many (Overload), Many to Many (No Overload) NAT
- NAT Loopback
- Port Triggering
- Port Forwarding (Virtual Server)
- Symmetric Port-Overloading NAT, Full-Cone NAT
- DMZ Host
- VPN Pass Through (PPTP, L2TP, IPSec)

### USB

- File Sharing (DLNA & Samba)
- Print Server

### Environment

- Operating temperature: 32~104°F (0~40°C)
- Relative humidity: 5~95% (non-condensing)

Note: Specifications are subject to change without notice.