



IT-5916

The **IT-5916** convinces with its robust and compact design and has the front connectors user-friendly in the upper part of the front panel.

In addition to a timeless look, the IT-5916 convinces with space for four fans, installation options for 3.5" & 2.5" hard drives and a sophisticated inner cage, which offers space for graphics cards up to a length of 35.5 cm. As standard, a SL-500K power supply is also installed.

The two USB 3.0 front connectors and the SDHC/MMC/MS card reader in the side edge of the front panel complete the positive overall package and make this Midi-Tower a true all-rounder.

- ✓ Design front panel
- ✓ incl. SL-500K power supply
- ✓ Graphics cards up to 35.5cm length
- ✓ SDHC/MMS/MS card reader

Specifications

Motherboard	ATX, µATX
Max. Drive Bays	5.25" external: 3 3.5" external: 1 2.5" internal: 2* 3.5" internal: 3*
Front Connectors	USB 3.0: 2 Card Reader: 1 Microphone: 1 Speaker: 1
Cooling System	Rear: 1x 80mm or 1x 120mm Front: 1x 120mm Side: 2x 120mm
Max CPU-Cooler height	145mm
Max Graphic card length	355mm
Packing Units	Shipping unit: 1 pcs Packing unit: 28 pcs
Warranty	Case 24 Months Warranty PSU 24 Months Guarantee
Article Number	88881316
EAN-Code	4260455644723
Scope of Delivery	Screw set Power cord Cable ties
Features	500W Power supply Reset button SDHC/MMC/MS Card Reader Upper slot bracket reusable Space for graphics cards with a length of 35.5cm Cable management USB 3.0 and Audio plug internally as standard block connectors Preparation for Kensington-Lock Lock loop HD-Audio

*can vary due to combinations

Dimensions and Weight

	Cage	Case	Package
Height	410mm	420mm	455mm
Width	180mm	200mm	230mm
Depth	370mm	400mm	465mm

Weight (net): 4.21kg
Weight (gross): 4.86kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	1x	40cm
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	1x	40cm
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	2x	40cm
S-ATA	3x	70cm
Floppy	1x	70cm
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	1x	-

Certification:

