



# Cloudera JDBC Driver for Impala

## Version 2.5.28



## **Important Notice**

© 2010-2015 Cloudera, Inc. All rights reserved.

Cloudera, the Cloudera logo, Cloudera Impala, Impala, and any other product or service names or slogans contained in this document, except as otherwise disclaimed, are trademarks of Cloudera and its suppliers or licensors, and may not be copied, imitated or used, in whole or in part, without the prior written permission of Cloudera or the applicable trademark holder.

Hadoop and the Hadoop elephant logo are trademarks of the Apache Software Foundation. All other trademarks, registered trademarks, product names and company names or logos mentioned in this document are the property of their respective owners. Reference to any products, services, processes or other information, by trade name, trademark, manufacturer, supplier or otherwise does not constitute or imply endorsement, sponsorship or recommendation thereof by us.

Complying with all applicable copyright laws is the responsibility of the user. Without limiting the rights under copyright, no part of this document may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of Cloudera.

Cloudera may have patents, patent applications, trademarks, copyrights, or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from Cloudera, the furnishing of this document does not give you any license to these patents, trademarks copyrights, or other intellectual property.

The information in this document is subject to change without notice. Cloudera shall not be liable for any damages resulting from technical errors or omissions which may be present in this document, or from use of this document.

**Cloudera, Inc.**  
**1001 Page Mill Road, Building 2**  
**Palo Alto, CA 94304-1008**  
[info@cloudera.com](mailto:info@cloudera.com)  
**US: 1-888-789-1488**  
**Intl: 1-650-843-0595**  
[www.cloudera.com](http://www.cloudera.com)

## **Release Information**

Version: 2.5.28

Date: October 2, 2015

# Table of Contents

<b>INTRODUCTION</b>	<b>5</b>
<b>SYSTEM REQUIREMENTS</b>	<b>5</b>
<b>CLOUDERA JDBC DRIVER FOR IMPALA FILES</b>	<b>6</b>
<b>USING THE CLOUDERA JDBC DRIVER FOR IMPALA</b>	<b>6</b>
SETTING THE CLASS PATH	7
INITIALIZING THE DRIVER CLASS	7
BUILDING THE CONNECTION URL	7
<b>JAVA SAMPLE CODE</b>	<b>8</b>
<b>CONFIGURING AUTHENTICATION</b>	<b>12</b>
USING NO AUTHENTICATION	12
USING KERBEROS	12
USING USER NAME	13
USING USER NAME AND PASSWORD	13
<b>CONFIGURING SSL</b>	<b>13</b>
<b>FEATURES</b>	<b>14</b>
SQL TRANSLATION	15
DATA TYPES	15
CATALOG AND SCHEMA SUPPORT	16
INTERFACES AND SUPPORTED METHODS	16
<b>CONTACT US</b>	<b>73</b>
<b>APPENDIX A CONFIGURING KERBEROS AUTHENTICATION FOR WINDOWS</b>	<b>74</b>
DOWNLOADING AND INSTALLING MIT KERBEROS FOR WINDOWS	74
USING THE MIT KERBEROS TICKET MANAGER TO GET TICKETS	74
USING THE DRIVER TO GET TICKETS	75
USING AN EXISTING SUBJECT TO AUTHENTICATE THE CONNECTION	76
<b>APPENDIX B DRIVER CONFIGURATION OPTIONS</b>	<b>79</b>
ALLOWSELF SIGNED CERTS	79
AUTHMECH	79
CAISSUED CERT NAMES MISMATCH	79
CATALOG SCHEMA SWITCH	80
DEFAULT STRING COLUMN LENGTH	80
DELEGATION UID	80
KRBHOST FQDN	81
KRBREALM	81
KRB SERVICE NAME	81

LOWERCASERESULTSETCOLUMNNAME .....	81
PREPAREDMETALIMITZERO .....	82
PWD .....	82
ROWSFETCHEDPERBLOCK .....	82
SOCKETTIMEOUT .....	83
SSL .....	83
SSLKEYSTORE .....	83
SSLKEYSTOREPWD .....	84
SSLTRUSTSTORE .....	84
SSLTRUSTSTOREPWD .....	84
UID .....	85
USENATIVEQUERY .....	85

## Introduction

The Cloudera JDBC Driver for Impala is used for direct SQL and Impala SQL access to Apache Hadoop / Impala distributions, enabling Business Intelligence (BI), analytics, and reporting on Hadoop / Impala-based data. The driver efficiently transforms an application's SQL query into the equivalent form in Impala SQL, which is a subset of SQL-92. If an application is Impala-aware, then the driver is configurable to pass the query through to the database for processing. The driver interrogates Impala to obtain schema information to present to a SQL-based application. Queries, including joins, are translated from SQL to Impala SQL. For more information about the differences between Impala SQL and SQL, see "Features" on page 14.

The Cloudera JDBC Driver for Impala complies with the JDBC 3.0, 4.0 and 4.1 data standards. JDBC is one of the most established and widely supported APIs for connecting to and working with databases. At the heart of the technology is the JDBC driver, which connects an application to the database. For more information about JDBC, see <http://www.simba.com/resources/data-access-standards-library>.

This guide is suitable for users who want to access data residing within Impala from their desktop environment. Application developers may also find the information helpful. Refer to your application for details on connecting via JDBC.

## System Requirements

Each computer where you use the Cloudera JDBC Driver for Impala must have Java Runtime Environment (JRE) installed. The version of JRE that must be installed depends on the version of the JDBC API you are using with the driver. Table 1 lists the required version of JRE for each version of the JDBC API.

Table 1. Cloudera JDBC Driver for Impala System Requirements

JDBC API Version	JRE Version
3.0	4.0 or 5.0
4.0	6.0 or later
4.1	7.0 or later

The driver is suitable for use with all versions of Cloudera Impala.

## Cloudera JDBC Driver for Impala Files

The Cloudera JDBC Driver for Impala is delivered in the following ZIP archives, where *version* is the version number of the driver:

- Cloudera\_ImpalaJDBC3\_*version*.zip
- Cloudera\_ImpalaJDBC4\_*version*.zip
- Cloudera\_ImpalaJDBC41\_*version*.zip

Each archive contains the driver supporting the JDBC API version indicated in the archive name.

The archives contain the following file and folder structure, where *LibVersion* is the version number of the library and *APIVersion* is the JDBC API version that the driver supports:

- ImpalaJDBCAPI*Version*
  - hive\_metastore.jar
  - hive\_service.jar
  - ImpalaJDBCAPI*Version*.jar
  - libfb303-*LibVersion*.jar
  - libthrift-*LibVersion*.jar
  - log4j-*LibVersion*.jar
  - ql.jar
  - slf4j-api-*LibVersion*.jar
  - slf4j-log4j12-*LibVersion*.jar
  - TCLIServiceClient.jar

## Using the Cloudera JDBC Driver for Impala

To access an Impala data warehouse using the Cloudera JDBC Driver for Impala, you need to set the following:

- Class path
- Driver class
- Connection URL

For sample code that demonstrates how to use the driver, see "Java Sample Code" on page 8.

**Important:**

The Cloudera JDBC Driver for Impala is a forward-only, read-only driver with no transaction support. Because the driver does not support transactions, auto-commit is always set to **true**

## Setting the Class Path

To use the Cloudera JDBC Driver for Impala, you must set the class path to include all the JAR files from the ZIP archive containing the driver that you are using.

The class path is the path that the Java Runtime Environment searches for classes and other resource files. For more information, see the topic *Setting the Class Path* in the Java SE Documentation at

<http://docs.oracle.com/javase/7/docs/technotes/tools/windows/classpath.html>

## Initializing the Driver Class

Before connecting to the Impala server, initialize the appropriate class for the Impala server and your application.

The following is a list of the classes used to connect the Cloudera JDBC Driver for Impala to Impala instances. The Driver classes extend `java.sql.Driver`, and the DataSource classes extend `javax.sql.DataSource` and `javax.sql.ConnectionPoolDataSource`

To support JDBC 3.0, classes with the following fully-qualified class names (FQCNs) are available:

- `com.cloudera.impala.jdbc3.Driver`
- `com.cloudera.impala.jdbc3.DataSource`

To support JDBC 4.0, classes with the following FQCNs are available:

- `com.cloudera.impala.jdbc4.Driver`
- `com.cloudera.impala.jdbc4.DataSource`

To support JDBC 4.1, classes with the following FQCNs are available:

- `com.cloudera.impala.jdbc41.Driver`
- `com.cloudera.impala.jdbc41.DataSource`

## Building the Connection URL

Use the connection URL to supply connection information to the data source that you are accessing. The connection URL for the Cloudera JDBC Driver for Impala takes the following form:

```
jdbc:Subprotocol://Host:Port
[/Schema];Property1=Value;Property2=Value;...
```

The placeholders in the connection URL are defined as follows:

- *Subprotocol* is the value **impala**
- *Host* is the DNS or IP address of the server hosting the Impala data warehouse.
- *Port* is the port to connect to on *Host*.
- *Schema* is the name of the schema/database you want to access. Specifying a schema is optional. If you do not specify a schema, then the schema named **default** is used.

- *Property* is any one of the connection properties that you can specify. For information about the properties available in the driver, see "Driver Configuration Options" on page 79.

**Important:**

Properties are case-sensitive. Do not duplicate properties in the connection URL.

For example, to connect to an Impala instance installed on the local computer and authenticate the connection using a user name and password, you would use the following connection URL:

`jdbc:impala://localhost:21050;AuthMech=3;UID=UserName;PWD=Password`

*UserName* and *Password* specify credentials for an existing user on the host running Impala.

For more information about the properties that you can use in the connection URL, see "Driver Configuration Options" on page 79.

## Java Sample Code

The following Java code provides an example demonstrating how to use the JDBC API to do the following:

- Register the Cloudera JDBC Driver for Impala
- Establish a connection to an Impala database
- Query the database
- Parse a result set
- Handle exceptions
- Clean up to avoid memory leakage

**Important:**

To use the Cloudera JDBC Driver for Impala in an application, you must include all the JAR files from the ZIP archive in the class path for your Java project.

```
// java.sql packages are required
import java.sql.*;
// java.math packages are required
import java.math.*;
class ClouderaJDBCImpalaExample {

    // Define a string as the fully qualified class name
    // (FQCN) of the desired JDBC driver
    static String JDBC_DRIVER = "com.cloudera.impala.jdbc3.Driver";
    // Define a string as the connection URL
```

```
private static final String CONNECTION_URL =
"jdbc:impala://192.168.1.1:21050";

public static void main(String[] args) {

    Connection con = null;
    Statement stmt = null;
    ResultSet rs = null;

    // Define a plain query
    String query = "SELECT store_sales, store_cost FROM
default.test LIMIT 20";
    // Define a parametrized query
    String prepQuery = "SELECT first_name, last_name, emp_id
FROM default.emp where store_id = ?";

    try {

        // Register the driver using the class name
        Class.forName(JDBC_DRIVER);

        // Establish a connection using the connection
        // URL
        con = DriverManager.getConnection(CONNECTION_URL);

        // Create a Statement object for sending SQL
        // statements to the database
        stmt = con.createStatement();

        // Execute the SQL statement
        rs = stmt.executeQuery(query);

        // Display a header line for output appearing in
        // the Console View
        System.out.printf("%20s%20s\r\n", "STORE SALES",
"STORE COST");

        // Step through each row in the result set
    }
}
```

## Java Sample Code

```
// returned from the database
while(rs.next()) {
    // Retrieve values from the row where the
    // cursor is currently positioned using
    // column names
    BigDecimal StoreSales = rs.getBigDecimal ("store_
sales");
    BigDecimal StoreCost = rs.getBigDecimal ("store_
cost");

    // Display values in columns 20 characters
    // wide in the Console View using the
    // Formatter
    System.out.printf("%20s%20s\r\n",
        StoreSales.toString(), StoreCost.toString());
}

// Create a prepared statement
PreparedStatement prep = m_conn.prepareStatement
(prepQuery);

// Bind the query parameter with a value
prep.setInt(1, 204);
// Execute the query
rs = prep.execute();
// Step through each row in the result set
// returned from the database
while(rs.next()) {
    // Retrieve values from the row where the
    // cursor is currently positioned using
    // column names
    String FirstName = rs.getString("first_name");
    String LastName = rs.getString("last_name");
    String EmployeeID = rs.getString("emp_id");

    // Display values in columns 20 characters
    // wide in the Console View using the
    // Formatter
```

```
        System.out.printf("%20s%20s%20s\r\n", FirstName,
                          LastName, EmployeeID);
    }

} catch (SQLException se) {
    // Handle errors encountered during interaction
    // with the data source
} catch (Exception e) {
    // Handle other errors
} finally {
    // Perform clean up
    try {
        if (rs != null) {
            rs.close();
        }
    } catch (SQLException se1) {
        // Log this
    }

    try {
        if (stmt != null) {
            stmt.close();
        }
    } catch (SQLException se2) {
        // Log this
    }
    try {
        if (prep != null) {
            prep.close();
        }
    } catch (SQLException se3) {
        // Log this
    }

    try {
        if (con != null) {
            con.close();
        }
    }
```

```
        }
    } catch (SQLException se4) {
        // Log this
    } // End try
} // End try
} // End main
} // End ClouderaJDBCImpalaExample
```

## Configuring Authentication

The Cloudera JDBC Driver for Impala supports the following authentication mechanisms:

- No Authentication
- Kerberos
- User Name
- User Name and Password

You configure the authentication mechanism that the driver uses to connect to Impala by specifying the relevant properties in the connection URL.

For information about configuring the authentication mechanism that Impala uses, refer to the Cloudera Impala documentation available at  
<http://www.cloudera.com/content/cloudera/en/documentation.html>.

For information about the properties you can use in the connection URL, see "Driver Configuration Options" on page 79.

**Note:**

In addition to authentication, you can configure the driver to connect over SSL. For more information, see "Configuring SSL" on page 13.

## Using No Authentication

**To configure a connection without authentication:**

- Set the AuthMech property to 0

For example:

```
jdbc:impala://localhost:21050;AuthMech=0
```

## Using Kerberos

Kerberos must be installed and configured before you can use this authentication mechanism. For information about configuring and operating Kerberos on Windows, see "Configuring Kerberos Authentication for Windows" on page 74. For other operating systems, refer to the MIT Kerberos documentation.

**To configure Kerberos authentication:**

1. Set the AuthMech property to 1
2. If your Kerberos setup does not define a default realm or if the realm of your Impala server is not the default, then set the KrbRealm property to the realm of the Impala server.

OR

To use the default realm defined in your Kerberos setup, do not set the KrbRealm property.

3. Set the KrbHostFQDN property to the fully qualified domain name of the Impala server host.
4. Set the KrbServiceName property to the service name of the Impala server.

For example:

```
jdbc:impala://localhost:21050;AuthMech=1;KrbRealm=EXAMPLE.COM;
KrbHostFQDN=impala.example.com;KrbServiceName=impala
```

**Using User Name**

This authentication mechanism requires a user name but does not require a password. The user name labels the session, facilitating database tracking.

**To configure User Name authentication:**

1. Set the AuthMech property to 2
2. Set the UID property to an appropriate user name for accessing the Impala server.

For example:

```
jdbc:impala://localhost:21050;AuthMech=2;UID=impala
```

**Using User Name and Password**

This authentication mechanism requires a user name and a password.

**To configure User Name and Password authentication:**

1. Set the AuthMech property to 3
2. Set the UID property to an appropriate user name for accessing the Impala server.
3. Set the PWD property to the password corresponding to the user name you provided in step 2.

For example:

```
jdbc:impala://localhost:21050;AuthMech=3;UID=impala;PWD=*****
```

**Configuring SSL**

If you are connecting to an Impala server that has Secure Sockets Layer (SSL) enabled, then you can configure the driver to connect to an SSL-enabled socket.

SSL connections require a KeyStore and a TrustStore. You can create a TrustStore and configure the driver to use it, or allow the driver to use one of the default TrustStores. If you do not configure the driver to use a specific TrustStore, then the driver uses the Java TrustStore `jssecacerts`. If `jssecacerts` is not available, then the driver uses `cacerts` instead.

### To configure SSL:

1. To create a KeyStore and configure the driver to use it, do the following:
  - a) Create a KeyStore containing your signed, trusted SSL certificate.
  - b) Set the `SSLKeyStore` property to the full path of the KeyStore, including the file name.
  - c) Set the `SSLKeyStorePwd` property to the password for the KeyStore.
2. Optionally, to create a TrustStore and configure the driver to use it, do the following:
  - a) Create a TrustStore containing your signed, trusted SSL certificate.
  - b) Set the `SSLTrustStore` property to the full path of the TrustStore, including the file name.
  - c) Set the `SSLTrustStorePwd` property to the password for the TrustStore.
3. Set the `SSL` property to 1
4. Optionally, to allow the SSL certificate used by the server to be self-signed, set the `AllowSelfSignedCerts` property to 1
5. Optionally, to allow the common name of a CA-issued certificate to not match the host name of the Impala server, set the `CAIssuedCertNamesMismatch` property to 1

**Note:**

For self-signed certificates, the driver always allows the common name of the certificate to not match the host name.

For example:

```
jdbc:impala://localhost:21050;AuthMech=3;SSL=1;  
SSLKeyStore=C:\\Users\\\\bsmith\\\\Desktop\\\\keystore.jks;  
SSLKeyStorePwd=*****;UID=impala;PWD=*****
```

**Note:**

For more information about the connection properties used in SSL connections, see "Driver Configuration Options" on page 79

## Features

More information is provided on the following features of the Cloudera JDBC Driver for Impala:

- "SQL Translation" on page 15
- "Data Types" on page 15
- "Catalog and Schema Support" on page 16

## SQL Translation

The Cloudera JDBC Driver for Impala is able to parse queries locally prior to sending them to the Impala server. This feature allows the driver to calculate query metadata without executing the query, support query parameters, and support extra SQL features such as JDBC escape sequences and additional scalar functions that are not available in the Impala-shell tool.

**Note:**

The driver does not support translation for queries that reference a field contained in a nested column (an ARRAY, MAP, or STRUCT column). To retrieve data from a nested column, ensure that the query is written in valid Impala SQL syntax.

## Data Types

The Cloudera JDBC Driver for Impala supports many common data formats, converting between Impala, SQL, and Java data types.

Table 2 lists the supported data type mappings.

**Table 2. Supported Data Types**

Impala Type	SQL Type	Java Type
ARRAY	VARCHAR	String
BIGINT	BIGINT	java.math.BigInteger
BINARY	VARBINARY	byte[]
BOOLEAN	BOOLEAN	Boolean
CHAR (Available only in CDH 5.2 or later)	CHAR	String
DATE	DATE	java.sql.Date
DECIMAL (Available only in CDH 5.1 or later)	DECIMAL	java.math.BigDecimal
DOUBLE (REAL is an alias for DOUBLE)	DOUBLE	Double
INT	INTEGER	Long

Impala Type	SQL Type	Java Type
FLOAT	REAL	Float
MAP	VARCHAR	String
SMALLINT	SMALLINT	Integer
STRUCT	VARCHAR	String
TINYINT	TINYINT	Short
TIMESTAMP	TIMESTAMP	java.sql.Timestamp
VARCHAR (Available only in CDH 5.2 or later)	VARCHAR	String

## Catalog and Schema Support

The Cloudera JDBC Driver for Impala supports both catalogs and schemas in order to make it easy for the driver to work with various JDBC applications. Since Impala only organizes tables into schemas/databases, the driver provides a synthetic catalog called “IMPALA” under which all of the schemas/databases are organized. The driver also maps the JDBC schema to the Impala schema/database.

**Note:**

Setting the CatalogSchemaSwitch connection property to 1 will cause Impala catalogs to be treated as schemas in the driver as a restriction for filtering.

## Interfaces and Supported Methods

The Cloudera JDBC Driver for Impala implements the following JDBC interfaces:

- "CallableStatement" on page 17
- "Connection" on page 26
- "DatabaseMetaData" on page 31
- "DataSource" on page 43
- "Driver" on page 44
- "ParameterMetaData" on page 45
- "PooledConnection" on page 46
- "PreparedStatement" on page 47
- "ResultSet" on page 52
- "ResultSetMetaData" on page 67
- "Statement" on page 69

However, the driver does not support every method from these interfaces. For information about whether a specific method is supported by the driver and which version of the JDBC API is the earliest version that supports the method, refer to the following sections.

The driver does **not** support the following JDBC features:

- Array
- Blob
- Clob
- Ref
- Savepoint
- SQLData
- SQLInput
- SQLOutput
- Struct

## CallableStatement

The CallableStatement interface extends the PreparedStatement interface.

Table 3 lists the methods that belong to the CallableStatement interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the CallableStatement interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/CallableStatement.html>

**Table 3. Methods in the CallableStatement Class Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Array getArray(int i)	3.0	No	
Array getArray(String parameterName)	3.0	No	
BigDecimal getBigDecimal (int parameterIndex)	3.0	Yes	
BigDecimal getBigDecimal (int parameterIndex, int scale)	3.0	Yes	Deprecated
BigDecimal getBigDecimal (String parameterName)	3.0	Yes	
Blob getBlob(int i)	3.0	No	
Blob getBlob(String parameterName)	3.0	No	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
boolean getBoolean(int parameterIndex)	3.0	Yes	
boolean getBoolean(String parameterName)	3.0	Yes	
byte getBytE(int parameterIndex)	3.0	Yes	
byte getBytE(String parameterName)	3.0	Yes	
byte[] getBytes(int parameterIndex)	3.0	Yes	
byte[] getBytes(String parameterName)	3.0	Yes	
Clob getBlob(int i)	3.0	No	
Clob getBlob(String parameterName)	3.0	No	
Date getDate(int parameterIndex)	3.0	Yes	
Date getDate(int parameterIndex, Calendar cal)	3.0	Yes	
Date getDate(String parameterName)	3.0	Yes	
Date getDate(String parameterName, Calendar cal)	3.0	Yes	
double getDouble(int parameterIndex)	3.0	Yes	
double getDouble(String parameterName)	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
float getFloat(int parameterIndex)	3.0	Yes	
float getFloat(String parameterName)	3.0	Yes	
int getInt(int parameterIndex)	3.0	Yes	
int getInt(String parameterName)	3.0	Yes	
long getLong(int parameterIndex)	3.0	Yes	
long getLong(String parameterName)	3.0	Yes	
Reader getNCharacterStream(int parameterIndex)	4.0	No	
Reader getNCharacterStream(String parameterName)	4.0	No	
NClob getNClob(int parameterIndex)	4.0	No	
NClob getNClob(String parameterName)	4.0	No	
String getNString(int parameterIndex)	4.0	No	
String getNString(String parameterName)	4.0	No	
Object getObject(int parameterIndex)	3.0	Yes	
<T> T getObject(int parameterIndex, Class<T>	4.1	No	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
type)			
Object getObject(int i, Map<String, Class<?>> map)	3.0	No	
Object getObject(String parameterName)	3.0	Yes	
<T> T getObject(String parameterName, Class<T> type)	4.1	No	
Object getObject(String parameterName, Map<String, Class<?>> map)	3.0	Yes	
Ref getRef(int i)	3.0	No	
Ref getRef(String parameterName)	3.0	No	
RowId getRowId(int parameterIndex)	4.0	No	
RowId getRowId(String parameterName)	4.0	No	
short getShort(int parameterIndex)	3.0	Yes	
short getShort(String parameterName)	3.0	Yes	
SQLXML getSQLXML(int parameterIndex)	4.0	No	
SQLXML getSQLXML(String parameterName)	4.0	No	
String getString(int parameterIndex)	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>String getString(String parameterName)</code>	3.0	Yes	
<code>Time getTime(int parameterIndex)</code>	3.0	Yes	
<code>Time getTime(int parameterIndex, Calendar cal)</code>	3.0	Yes	
<code>Time getTime(String parameterName)</code>	3.0	Yes	
<code>Time getTime(String parameterName, Calendar cal)</code>	3.0	Yes	
<code>Timestamp getTimestamp (int parameterIndex)</code>	3.0	Yes	
<code>Timestamp getTimestamp (int parameterIndex, Calendar cal)</code>	3.0	Yes	
<code>Timestamp getTimestamp (String parameterName)</code>	3.0	Yes	
<code>Timestamp getTimestamp (String parameterName, Calendar cal)</code>	3.0	Yes	
<code>URL getURL(int parameterIndex)</code>	3.0	No	
<code>URL getURL(String parameterName)</code>	3.0	No	
<code>void registerOutParameter(int parameterIndex, int sqlType)</code>	3.0	Yes	
<code>void</code>	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>registerOutParameter(int parameterIndex, int sqlType, int scale)</code>			
<code>void registerOutParameter(int paramIndex, int sqlType, String typeName)</code>	3.0	Yes	
<code>void registerOutParameter(String parameterName, int sqlType)</code>	3.0	Yes	
<code>void registerOutParameter(String parameterName, int sqlType, int scale)</code>	3.0	Yes	
<code>void registerOutParameter(String parameterName, int sqlType, String typeName)</code>	3.0	Yes	
<code>void setAsciiStream(String parameterName, InputStream x)</code>	4.0	Yes	
<code>void setAsciiStream(String parameterName, InputStream x, int length)</code>	3.0	Yes	
<code>void setAsciiStream(String parameterName, InputStream x, long length)</code>	4.0	Yes	
<code>void setBigDecimal(String parameterName, BigDecimal x)</code>	3.0	Yes	
<code>void setBinaryStream</code>	4.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
(String parameterName, InputStream x)			
setBinaryStream(String parameterName, InputStream x, int length)	3.0	Yes	
void setBinaryStream (String parameterName, InputStream x, long length)	4.0	Yes	
void setBlob(String parameterName, Blob x)	4.0	Yes	
void setBlob(String parameterName, InputStream inputStream)	4.0	Yes	
void setBlob(String parameterName, InputStream inputStream, long length)	4.0	Yes	
void setBoolean(String parameterName, boolean x)	3.0	Yes	
void setByte(String parameterName, byte x)	3.0	Yes	
void setBytes(String parameterName, byte[] x)	3.0	Yes	
void setCharacterStream (String parameterName, Reader reader)	4.0	Yes	
void setCharacterStream (String parameterName, Reader reader, int length)	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setCharacterStream (String parameterName, Reader reader, long length)</code>	4.0	Yes	
<code>void setClob(String parameterName, Clob x)</code>	4.0	Yes	
<code>void setClob(String parameterName, Reader reader)</code>	4.0	Yes	
<code>void setClob(String parameterName, Reader reader, long length)</code>	4.0	Yes	
<code>void setDate(String parameterName, Date x)</code>	3.0	Yes	
<code>void setDate(String parameterName, Date x, Calendar cal)</code>	3.0	Yes	
<code>void setDouble(String parameterName, double x)</code>	3.0	Yes	
<code>void setFloat(String parameterName, float x)</code>	3.0	Yes	
<code>void setInt(String parameterName, int x)</code>	3.0	Yes	
<code>void setLong(String parameterName, long x)</code>	3.0	Yes	
<code>void setNCharacterStream (String parameterName, Reader value)</code>	4.0	Yes	
<code>void setNCharacterStream (String parameterName, Reader value, long length)</code>	4.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
void setNClob(String parameterName, NClob value)	4.0	Yes	
void setNClob(String parameterName, Reader reader)	4.0	Yes	
void setNClob(String parameterName, Reader reader, long length)	4.0	Yes	
void setNString(String parameterName, String value)	4.0	Yes	
void setNull(String parameterName, int sqlType)	3.0	Yes	
void setNull(String parameterName, int sqlType, String typeName)	3.0	Yes	
void setObject(String parameterName, Object x)	3.0	Yes	
void setObject(String parameterName, Object x, int targetSqlType)	3.0	Yes	
void setObject(String parameterName, Object x, int targetSqlType, int scale)	3.0	Yes	
void setRowId(String parameterName, RowId x)	4.0	Yes	
void setShort(String parameterName, short x)	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
void setSQLXML(String parameterName, SQLXML xmlObject)	4.0	Yes	
void setString(String parameterName, String x)	3.0	Yes	
void setTime(String parameterName, Time x)	3.0	Yes	
void setTime(String parameterName, Time x, Calendar cal)	3.0	Yes	
void setTimestamp(String parameterName, Timestamp x)	3.0	Yes	
void setTimestamp(String parameterName, Timestamp x, Calendar cal)	3.0	Yes	
void setURL(String parameterName, URL val)	3.0	Yes	
boolean wasNull()	3.0	Yes	
boolean isWrapperFor (Class<?> iface)	4.0	Yes	
<T> T unwrap(Class<T> iface)	4.0	Yes	

## Connection

Table 4 lists the methods that belong to the Connection interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the Connection interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/Connection.html>

**Table 4. Methods in the Connection Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
void clearWarnings()	3.0	Yes	
void close()	3.0	Yes	
void commit()	3.0	Yes	Auto-commit cannot be set to false because it is hard-coded as true
Array createArrayOf (String typeName, Object [] elements)	4.0	No	
Blob createBlob()	4.0	No	
Clob createClob()	4.0	No	
NClob createNClob()	4.0	No	
SQLXML createSQLXML()	4.0	No	
Statement createStatement ()	3.0	Yes	
Statement createStatement (int resultSetType, int resultSetConcurrency)	3.0	No	
Statement createStatement (int resultSetType, int resultSetConcurrency, int resultSetHoldability)	3.0	No	
Struct createStruct (String typeName, Object [] attributes)	4.0	No	
boolean getAutoCommit()	3.0	Yes	Hard-coded to true
String getCatalog()	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Properties getClientInfo()	4.0	Yes	
String getClientInfo(String name)	4.0	Yes	
int getHoldability()	3.0	Yes	Hard-coded to CLOSE_CURSORS_AT_COMMIT
DatabaseMetaData getMetaData()	3.0	Yes	
int getNetworkTimeout()	4.1	No	
String getSchema()	4.1	Yes	The returned schema name does not always match the one used by statements. Statements use the schema name defined in the connection URL.
int getTransactionIsolation()	3.0	Yes	Hard-coded to TRANSACTION_READ_UNCOMMITTED
Map<String, Class<?>> getTypeMap()	3.0	No	
SQLWarning getWarnings()	3.0	Yes	
boolean isClosed()	3.0	Yes	
boolean isReadOnly()	3.0	Yes	Returns true
boolean isValid(int timeout)	4.0	Yes	
String nativeSQL(String sql)	3.0	Yes	
CallableStatement prepareCall(String sql)	3.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
CallableStatement prepareCall(String sql, int resultSetType, int resultSetConcurrency)	3.0	No	
CallableStatement prepareCall(String sql, int resultSetType, int resultSetConcurrency, int resultSetHoldability)	3.0	No	
PreparedStatement prepareStatement(String sql)	3.0	Yes	
PreparedStatement prepareStatement(String sql, int autoGeneratedKeys)	3.0	No	
PreparedStatement prepareStatement(String sql, int[] columnIndexes)	3.0	No	
PreparedStatement prepareStatement(String sql, int resultSetType, int resultSetConcurrency)	3.0	No	
PreparedStatement prepareStatement(String sql, int resultSetType, int resultSetConcurrency, int resultSetHoldability)	3.0	No	
PreparedStatement prepareStatement(String sql, String[] columnNames)	3.0	No	
void releaseSavepoint (Savepoint savepoint)	3.0	No	Savepoints are not available because transactions are not supported.

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
void rollback()	3.0	No	Savepoints are not available because transactions are not supported.
void rollback(Savepoint savepoint)	3.0	No	Savepoints are not available because transactions are not supported.
void setAutoCommit(boolean autoCommit)	3.0	Yes	Ignored because auto-commit is hard-coded to true
void setCatalog(String catalog)	3.0	Yes	
void setClientInfo(Properties properties)	4.0	Yes	
void setClientInfo(String name, String value)	4.0	Yes	
void setHoldability(int holdability)	3.0	Yes	
void setNetworkTimeout(Executor executor, int milliseconds)	4.1	No	
void setReadOnly(boolean readOnly)	3.0	Yes	
Savepoint setSavepoint()	3.0	No	Savepoints are not available because transactions are not supported.
Savepoint setSavepoint(String name)	3.0	No	Savepoints are not available because transactions are not supported.
void setSchema(String schema)	4.1	Yes	Does not actually change the schema name used by newly created statements;

Method	Supported Since JDBC Version	Supported by the Driver	Notes
			only changes the value returned by getSchema()
void setTransactionIsolation (int level)	3.0	Yes	
void setTypeMap (Map<String, Class<?>> map)	3.0	No	
boolean isWrapperFor (Class<?> iface)	4.0	Yes	
<T> T unwrap(Class<T> iface)	4.0	Yes	

## DatabaseMetaData

Table 5 lists the methods that belong to the DatabaseMetaData interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the DatabaseMetaData interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/DatabaseMetaData.html>

Table 5. Methods in the DatabaseMetaData Interface

Method	Supported Since JDBC Version	Supported by the Driver	Notes
boolean allProceduresAreCallable()	3.0	Yes	Returns true
boolean allTablesAreSelectable()	3.0	Yes	Returns true
boolean autoCommitFailureClosesAllResultSets()	4.0	Yes	Returns true

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
boolean dataDefinitionCausesTransactionCommit()	3.0	Yes	Returns false
boolean dataDefinitionIgnoredInTransactions()	3.0	Yes	Returns false
boolean deletesAreDetected(int type)	3.0	Yes	Returns true
boolean doesMaxRowSizeIncludeBlobs()	3.0	Yes	Returns false
boolean generatedKeyAlwaysReturned()	4.1	Yes	
ResultSet getAttributes(String catalog, String schemaPattern, String typeNamePattern, String attributeNamePattern)	3.0	Yes	
ResultSet getBestRowIdentifier(String catalog, String schema, String table, int scope, boolean nullable)	3.0	Yes	
ResultSet getCatalogs()	3.0	Yes	
String getCatalogSeparator()	3.0	Yes	
String getCatalogTerm()	3.0	Yes	
ResultSet getClientInfoProperties()	4.0	Yes	
ResultSet getColumnPrivileges(String catalog, String schema, String table, String columnNamePattern)	3.0	Yes	
ResultSet getColumns(String catalog, String schemaPattern, String tableNamePattern, String columnNamePattern)	3.0	Yes	
Connection getConnection()	3.0	Yes	

Method	Sup-ported Since JDBC Ver-sion	Sup-ported by the Driver	Notes
ResultSet getCrossReference(String primaryCatalog, String primarySchema, String primaryTable, String foreignCatalog, String foreignSchema, String foreignTable)	3.0	Yes	
int getDatabaseMajorVersion()	3.0	Yes	
int getDatabaseMinorVersion()	3.0	Yes	
String getDatabaseProductName()	3.0	Yes	Hard-coded to Cloudera Impala
String getDatabaseProductVersion()	3.0	Yes	
int getDefaultTransactionIsolation()	3.0	Yes	Hard-coded to TRANSACTION_READ_UNCOMMITTED
int getDriverMajorVersion()	3.0	Yes	
int getDriverMinorVersion()	3.0	Yes	
String getDriverName()	3.0	Yes	Hard-coded to ImpalaJDBC
String getDriverVersion()	3.0	Yes	
ResultSet getExportedKeys(String catalog, String schema, String table)	3.0	Yes	
String getExtraNameCharacters()	3.0	Yes	Returns an empty String.
ResultSet getFunctionColumns(String catalog, String schemaPattern, String functionNamePattern, String columnNamePattern)	4.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>ResultSet getFunctions(String catalog, String schemaPattern, String functionNamePattern)</code>	4.0	Yes	
<code>String getIdentifierQuoteString()</code>	3.0	Yes	Returns a backquote (`)
<code>ResultSet getImportedKeys(String catalog, String schema, String table)</code>	3.0	Yes	
<code>ResultSet getIndexInfo(String catalog, String schema, String table, boolean unique, boolean approximate)</code>	3.0	Yes	
<code>int getJDBCMajorVersion()</code>	3.0	Yes	
<code>int getJDBCMinorVersion()</code>	3.0	Yes	
<code>int getMaxBinaryLiteralLength()</code>	3.0	Yes	Returns 0
<code>int getMaxCatalogNameLength()</code>	3.0	Yes	Returns 128
<code>int getMaxCharLiteralLength()</code>	3.0	Yes	Returns 0
<code>int getMaxColumnNameLength()</code>	3.0	Yes	Returns 128
<code>int getMaxColumnsInGroupBy()</code>	3.0	Yes	Returns 0
<code>int getMaxColumnsInIndex()</code>	3.0	Yes	Returns 0
<code>int getMaxColumnsInOrderBy()</code>	3.0	Yes	Returns 0
<code>int getMaxColumnsInSelect()</code>	3.0	Yes	Returns 0
<code>int getMaxColumnsInTable()</code>	3.0	Yes	Returns 0
<code>int getMaxConnections()</code>	3.0	Yes	Returns 0
<code>int getMaxCursorNameLength()</code>	3.0	Yes	Returns 0

Method	Supported Since JDBC Version	Supported by the Driver	Notes
int getMaxIndexLength()	3.0	Yes	Returns 0
int getMaxProcedureNameLength()	3.0	Yes	Returns 0
int getMaxRowSize()	3.0	Yes	Returns 0
int getMaxSchemaNameLength()	3.0	Yes	Returns 128
int getMaxStatementLength()	3.0	Yes	Returns 0
int getMaxStatements()	3.0	Yes	Returns 0
int getMaxTableNameLength()	3.0	Yes	Returns 128
int getMaxTablesInSelect()	3.0	Yes	Returns 0
int getMaxUserNameLength()	3.0	Yes	Returns 0
String getNumericFunctions()	3.0	Yes	Returns the Numeric Functions list from the specification related to the JDBC version of the driver.
ResultSet getPrimaryKeys(String catalog, String schema, String table)	3.0	Yes	
ResultSet getProcedureColumns(String catalog, String schemaPattern, String procedureNamePattern, String columnNamePattern)	3.0	Yes	
ResultSet getProcedures(String catalog, String schemaPattern, String procedureNamePattern)	3.0	Yes	
String getProcedureTerm()	3.0	Yes	Returns

Method	Supported Since JDBC Version	Supported by the Driver	Notes
			procedure
ResultSet getPseudoColumns(String catalog, String schemaPattern, String tableNamePattern, String columnNamePattern)	4.1	Yes	
int getResultSetHoldability()	3.0	Yes	Returns CLOSE_CURSORS_AT_COMMIT
RowIdLifetime getRowIdLifetime()	4.0	Yes	Returns ROWID_UNSUPPORTED
ResultSet getSchemas()	3.0	Yes	
ResultSet getSchemas(String catalog, String schemaPattern)	4.0	Yes	
String getSchemaTerm()	3.0	Yes	Returns schema
String getSearchStringEscape()	3.0	Yes	Returns a backslash (\)
String getSQLKeywords()	3.0	Yes	Returns an empty String.
int getSQLStateType()	3.0	Yes	Returns sqlStateSQL99
String getStringFunctions()	3.0	Yes	Returns the String Functions list from the specification related to the JDBC version of the driver.
ResultSet getSuperTables(String	3.0	Yes	

Method	Sup-ported Since JDBC Ver-sion	Sup-ported by the Driver	Notes
catalog, String schemaPattern, String tableNamePattern)			
ResultSet getSuperTypes(String catalog, String schemaPattern, String typeNamePattern)	3.0	Yes	
String getSystemFunctions()	3.0	Yes	Returns DATABASE,IFNU LL,USER
ResultSet getTablePrivileges(String catalog, String schemaPattern, String tableNamePattern)	3.0	Yes	
ResultSet getTables(String catalog, String schemaPattern, String tableNamePattern, String[] types)	3.0	Yes	
ResultSet getTableTypes()	3.0	Yes	
String getTimeDateFunctions()	3.0	Yes	Returns the Time and Date Functions list from the specification related to the JDBC version of the driver.
ResultSet getTypeInfo()	3.0	Yes	
ResultSet getUDTs(String catalog, String schemaPattern, String typeNamePattern, int[] types)	3.0	Yes	
String getURL()	3.0	Yes	
String getUsername()	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
ResultSet getVersionColumns(String catalog, String schema, String table)	3.0	Yes	
boolean insertsAreDetected(int type)	3.0	Yes	
boolean isCatalogAtStart()	3.0	Yes	
boolean isReadOnly()	3.0	Yes	Returns true
boolean locatorsUpdateCopy()	3.0	Yes	Returns false
boolean nullPlusNonNullIsNull()	3.0	Yes	Returns true
boolean nullsAreSortedAtEnd()	3.0	Yes	Returns false
boolean nullsAreSortedAtStart()	3.0	Yes	Returns false
boolean nullsAreSortedHigh()	3.0	Yes	Returns false
boolean nullsAreSortedLow()	3.0	Yes	Returns true
boolean othersDeletesAreVisible(int type)	3.0	Yes	
boolean othersInsertsAreVisible(int type)	3.0	Yes	
boolean othersUpdatesAreVisible(int type)	3.0	Yes	
boolean ownDeletesAreVisible(int type)	3.0	Yes	
boolean ownInsertsAreVisible(int type)	3.0	Yes	
boolean ownUpdatesAreVisible(int type)	3.0	Yes	
boolean storesLowerCaseIdentifiers()	3.0	Yes	Returns false
boolean storesLowerCaseQuotedIdentifiers()	3.0	Yes	Returns false

Method	Supported Since JDBC Version	Supported by the Driver	Notes
boolean storesMixedCaseIdentifiers()	3.0	Yes	Returns true
boolean storesMixedCaseQuotedIdentifiers()	3.0	Yes	Returns true
boolean storesUpperCaseIdentifiers()	3.0	Yes	Returns false
boolean storesUpperCaseQuotedIdentifiers()	3.0	Yes	Returns false
boolean supportsAlterTableWithAddColumn()	3.0	Yes	Returns false
boolean supportsAlterTableWithDropColumn()	3.0	Yes	Returns false
boolean supportsANSI92EntryLevelSQL()	3.0	Yes	Returns true
boolean supportsANSI92FullSQL()	3.0	Yes	Returns false
boolean supportsANSI92IntermediateSQL()	3.0	Yes	Returns false
boolean supportsBatchUpdates()	3.0	Yes	Returns false
boolean supportsCatalogsInDataManipulation()	3.0	Yes	Returns true
boolean supportsCatalogsInIndexDefinitions()	3.0	Yes	Returns true
boolean supportsCatalogsInPrivilegeDefinitions()	3.0	Yes	Returns true
boolean supportsCatalogsInProcedureCalls()	3.0	Yes	Returns true
boolean supportsCatalogsInTableDefinitions()	3.0	Yes	Returns true

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
boolean supportsColumnAliasing()	3.0	Yes	Returns true
boolean supportsConvert()	3.0	Yes	Returns true
boolean supportsConvert(int fromType, int toType)	3.0	Yes	
boolean supportsCoreSQLGrammar()	3.0	Yes	Returns true
boolean supportsCorrelatedSubqueries()	3.0	Yes	Returns true
boolean supportsDataDefinitionAndDataManipulationTransactions()	3.0	Yes	Returns false
boolean supportsDataManipulationTransactionsOnly()	3.0	Yes	Returns false
boolean supportsDifferentTableCorrelationNames()	3.0	Yes	Returns false
boolean supportsExpressionsInOrderBy()	3.0	Yes	Returns true
boolean supportsExtendedSQLGrammar()	3.0	Yes	Returns false
boolean supportsFullOuterJoins()	3.0	Yes	Returns true
boolean supportsGetGeneratedKeys()	3.0	Yes	Returns false
boolean supportsGroupBy()	3.0	Yes	Returns true
boolean supportsGroupByBeyondSelect()	3.0	Yes	Returns true
boolean supportsGroupByUnrelated()	3.0	Yes	Returns false
boolean supportsIntegrityEnhancementFacility()	3.0	Yes	Returns false

Method	Sup-ported Since JDBC Ver-sion	Sup-ported by the Driver	Notes
boolean supportsLikeEscapeClause()	3.0	Yes	Returns true
boolean supportsLimitedOuterJoins()	3.0	Yes	Returns false
boolean supportsMinimumSQLGrammar()	3.0	Yes	Returns true
boolean supportsMixedCaseIdentifiers()	3.0	Yes	Returns false
boolean supportsMixedCaseQuotedIdentifiers()	3.0	Yes	Returns true
boolean supportsMultipleOpenResults()	3.0	Yes	Returns false
boolean supportsMultipleResultSets()	3.0	Yes	Returns false
boolean supportsMultipleTransactions()	3.0	Yes	Returns true
boolean supportsNamedParameters()	3.0	Yes	Returns false
boolean supportsNonNullableColumns()	3.0	Yes	Returns false
boolean supportsOpenCursorsAcrossCommit()	3.0	Yes	Returns false
boolean supportsOpenCursorsAcrossRollback()	3.0	Yes	Returns false
boolean supportsOpenStatementsAcrossCommit()	3.0	Yes	Returns true
boolean supportsOpenStatementsAcrossRollback()	3.0	Yes	Returns true
boolean supportsOrderByUnrelated()	3.0	Yes	Returns false
boolean supportsOuterJoins()	3.0	Yes	Returns false
boolean supportsPositionedDelete()	3.0	Yes	Returns false

Method	Supported Since JDBC Version	Supported by the Driver	Notes
boolean supportsPositionedUpdate()	3.0	Yes	Returns false
boolean supportsResultSetConcurrency(int type, int concurrency)	3.0	Yes	
boolean supportsResultSetHoldability(int holdability)	3.0	Yes	
boolean supportsResultSetType(int type)	3.0	Yes	
boolean supportsSavepoints()	3.0	Yes	Returns false
boolean supportsSchemasInDataManipulation()	3.0	Yes	Returns true
boolean supportsSchemasInIndexDefinitions()	3.0	Yes	Returns true
boolean supportsSchemasInPrivilegeDefinitions()	3.0	Yes	Returns true
boolean supportsSchemasInProcedureCalls()	3.0	Yes	Returns false
boolean supportsSchemasInTableDefinitions()	3.0	Yes	Returns true
boolean supportsSelectForUpdate()	3.0	Yes	Returns false
boolean supportsStatementPooling()	3.0	Yes	Returns false
boolean supportsStoredFunctionsUsingCallSyntax()	4.0	Yes	Returns false
boolean supportsStoredProcedures()	3.0	Yes	Returns true
boolean supportsSubqueriesInComparisons()	3.0	Yes	Returns true

Method	Supported Since JDBC Version	Supported by the Driver	Notes
boolean supportsSubqueriesInExists()	3.0	Yes	Returns true
boolean supportsSubqueriesInIns()	3.0	Yes	Returns true
boolean supportsSubqueriesInQuantifieds()	3.0	Yes	Returns true
boolean supportsTableCorrelationNames()	3.0	Yes	Returns true
boolean supportsTransactionIsolationLevel(int level)	3.0	Yes	
boolean supportsTransactions()	3.0	Yes	Returns false
boolean supportsUnion()	3.0	Yes	Returns true
boolean supportsUnionAll()	3.0	Yes	Returns true
boolean updatesAreDetected(int type)	3.0	Yes	Returns true
boolean usesLocalFilePerTable()	3.0	Yes	Returns false
boolean usesLocalFiles()	3.0	Yes	Returns false
boolean isWrapperFor(Class<?> iface)	4.0	Yes	
<T> T unwrap(Class<T> iface)	4.0	Yes	

## DataSource

Table 6 lists the methods that belong to the `DataSource` interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the `DataSource` interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/javax/sql/DataSource.html>

**Table 6. Methods in the DataSource Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Connection getConnection()	3.0	Yes	
Connection getConnection(String username, String password)	3.0	Yes	
int getLoginTimeout()	3.0	Yes	
PrintWriter getLogWriter()	3.0	Yes	
Logger getParentLogger()	4.1	No	The driver does not use java.util.logging
void setLoginTimeout(int seconds)	3.0	Yes	
void setLogWriter(PrintWriter out)	3.0	Yes	
boolean isWrapperFor(Class<?> iface)	4.0	Yes	
<T> T unwrap(Class<T> iface)	4.0	Yes	

## Driver

Table 7 lists the methods that belong to the Driver interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the Driver interface, see the Java API documentation available at <http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/Driver.html>

**Table 7. Methods in the Driver Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
boolean acceptsURL (String url)	3.0	Yes	
Connection connect (String url, Properties info)	3.0	Yes	
int getMajorVersion()	3.0	Yes	
int getMinorVersion()	3.0	Yes	
Logger getParentLogger()	4.1	No	
DriverPropertyInfo[] getPropertyInfo(String url, Properties info)	3.0	Yes	
boolean jdbcCompliant()	3.0	Yes	

## ParameterMetaData

Table 8 lists the methods that belong to the ParameterMetaData interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the ParameterMetaData interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/ParameterMetaData.html>

**Table 8. Methods in the ParameterMetaData Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
String getParameterClassName (int param)	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
int getParameterCount()	3.0	Yes	
int getParameterMode(int param)	3.0	Yes	
int getParameterType(int param)	3.0	Yes	
String getParameterTypeName(int param)	3.0	Yes	
int getPrecision(int param)	3.0	Yes	
int getScale(int param)	3.0	Yes	
int isNullable(int param)	3.0	Yes	
boolean isSigned(int param)	3.0	Yes	
boolean isWrapperFor (Class<?> iface)	4.0	Yes	
<T> T unwrap(Class<T> iface)	4.0	Yes	

## PooledConnection

Table 9 lists the methods that belong to the PooledConnection interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the PooledConnection interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/javax/sql/PooledConnection.html>

**Table 9. Methods in the PooledConnection Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void addConnectionEventListener (ConnectionEventListener listener)</code>	3.0	Yes	
<code>void addStatementEventListener (StatementEventListener listener)</code>	4.0	Yes	
<code>void close()</code>	3.0	Yes	
<code>Connection getConnection()</code>	3.0	Yes	
<code>void removeConnectionEventListener (ConnectionEventListener listener)</code>	3.0	Yes	
<code>void removeStatementEventListener (StatementEventListener listener)</code>	4.0	Yes	Removes the specified StatementEventListener from the list of components that will be notified when the driver detects that a PreparedStatement has been closed or is invalid.

## PreparedStatement

The PreparedStatement interface extends the Statement interface.

Table 10 lists the methods that belong to the PreparedStatement interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the PooledConnection interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/PreparedStatement.html>

**Table 10. Methods in the PreparedStatement Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
void addBatch()	3.0	Yes	
void clearParameters()	3.0	Yes	
boolean execute()	3.0	Yes	
ResultSet executeQuery()	3.0	Yes	
int executeUpdate()	3.0	Yes	
ResultSetMetaData getMetaData()	3.0	Yes	
ParameterMetaData getParameterMetaData()	3.0	Yes	
void setArray(int parameterIndex, Array x)	3.0	No	
void setAsciiStream(int parameterIndex, InputStream x)	4.0	Yes	
void setAsciiStream(int parameterIndex, InputStream x, int length)	3.0	Yes	
void setAsciiStream(int parameterIndex, InputStream x, long length)	4.0	Yes	
void setBigDecimal(int parameterIndex, BigDecimal x)	3.0	Yes	
void setBinaryStream(int parameterIndex, InputStream x)	4.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setBinaryStream(int parameterIndex, InputStream x, int length)</code>	3.0	Yes	
<code>void setBinaryStream(int parameterIndex, InputStream x, long length)</code>	4.0	Yes	
<code>void setBlob(int parameterIndex, Blob x)</code>	3.0	No	
<code>void setBlob(int parameterIndex, InputStream inputStream)</code>	4.0	No	
<code>void setBlob(int parameterIndex, InputStream inputStream, long length)</code>	4.0	No	
<code>void setBoolean(int parameterIndex, boolean x)</code>	3.0	Yes	
<code>void setByte(int parameterIndex, byte x)</code>	3.0	Yes	
<code>void setBytes(int parameterIndex, byte[] x)</code>	3.0	Yes	
<code>void setCharacterStream(int parameterIndex, Reader reader)</code>	4.0	Yes	
<code>void setCharacterStream(int parameterIndex, Reader reader, int length)</code>	3.0	Yes	
<code>void setCharacterStream(int parameterIndex,</code>	4.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Reader reader, long length)			
void setClob(int parameterIndex, Clob x)	3.0	No	
void setClob(int parameterIndex, Reader reader)	4.0	No	
void setClob(int parameterIndex, Reader reader, long length)	4.0	No	
void setDate(int parameterIndex, Date x)	3.0	Yes	
void setDate(int parameterIndex, Date x, Calendar cal)	3.0	Yes	
void setDouble(int parameterIndex, double x)	3.0	Yes	
void setFloat(int parameterIndex, float x)	3.0	Yes	
void setInt(int parameterIndex, int x)	3.0	Yes	
void setLong(int parameterIndex, long x)	3.0	Yes	
void setNCharacterStream (int parameterIndex, Reader value)	4.0	No	
void setNCharacterStream (int parameterIndex, Reader value, long length)	4.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
void setNClob(int parameterIndex, NClob value)	4.0	No	
void setNClob(int parameterIndex, Reader reader)	4.0	No	
void setNClob(int parameterIndex, Reader reader, long length)	4.0	No	
void setNString(int parameterIndex, String value)	4.0	No	
void setNull(int paramIndex, int sqlType, String typeName)	3.0	Yes	
void setObject(int parameterIndex, Object x)	3.0	Yes	
void setObject(int parameterIndex, Object x, int targetSqlType)	3.0	Yes	
void setObject(int parameterIndex, Object x, int targetSqlType, int scale)	3.0	Yes	
void setRef(int parameterIndex, Ref x)	3.0	No	
void setRowId(int parameterIndex, RowId x)	4.0	No	
void setShort(int parameterIndex, short x)	3.0	No	
void setSQLXML(int	4.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
parameterIndex, SQLXML xmlObject)			
void setString(int parameterIndex, String x)	3.0	Yes	
void setTime(int parameterIndex, Time x)	3.0	Yes	
void setTime(int parameterIndex, Time x, Calendar cal)	3.0	Yes	
void setTimestamp(int parameterIndex, Timestamp x)	3.0	Yes	
void setTimestamp(int parameterIndex, Timestamp x, Calendar cal)	3.0	Yes	
void setUnicodeStream (int parameterIndex, InputStream x, int length)	3.0	Yes	Deprecated
void setURL(int parameterIndex, URL x)	3.0	No	
boolean isWrapperFor (Class<?> iface)	4.0	Yes	
<T> T unwrap(Class<T> iface)	4.0	Yes	

## ResultSet

Table 11 lists the methods that belong to the ResultSet interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the `ResultSet` interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/ResultSet.html>

**Table 11. Methods in the `ResultSet` Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>boolean absolute(int row)</code>	3.0	No	
<code>void afterLast()</code>	3.0	No	
<code>void beforeFirst()</code>	3.0	No	
<code>void cancelRowUpdates()</code>	3.0	No	Not valid because the driver is read-only.
<code>void clearWarnings()</code>	3.0	Yes	
<code>void close()</code>	3.0	Yes	
<code>void deleteRow()</code>	3.0	No	Not valid because the driver is read-only.
<code>int findColumn(String columnName)</code>	3.0	Yes	
<code>boolean first()</code>	3.0	No	
<code>Array getArray(int i)</code>	3.0	No	
<code>Array getArray(String colName)</code>	3.0	No	
<code>InputStream getAsciiStream(int columnIndex)</code>	3.0	Yes	
<code>InputStream getAsciiStream(String columnName)</code>	3.0	Yes	
<code>BigDecimal getBigDecimal(int columnIndex)</code>	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>BigDecimal getBigDecimal(int columnIndex, int scale)</code>	3.0	Yes	Deprecated
<code>BigDecimal getBigDecimal(String columnName)</code>	3.0	Yes	
<code>BigDecimal getBigDecimal(String columnName, int scale)</code>	3.0	Yes	Deprecated
<code>InputStream getBinaryStream(int columnIndex)</code>	3.0	Yes	
<code>InputStream getBinaryStream(String columnName)</code>	3.0	Yes	
<code>Blob getBlob(int i)</code>	3.0	No	
<code>Blob getBlob(String colName)</code>	3.0	No	
<code>boolean getBoolean(int columnIndex)</code>	3.0	Yes	
<code>boolean getBoolean(String columnName)</code>	3.0	Yes	
<code>getByte(int columnIndex)</code>	3.0	Yes	
<code>byte getByte(String columnName)</code>	3.0	Yes	
<code>byte[] getBytes(int columnIndex)</code>	3.0	Yes	
<code>byte[] getBytes(String columnName)</code>	3.0	Yes	
<code>Reader getCharacterStream(int columnIndex)</code>	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Reader getCharacterStream (String columnName)	3.0	Yes	
Clob getClob(int i)	3.0	No	
Clob getClob(String colName)	3.0	No	
int getConcurrency()	3.0	Yes	
String getCursorName()	3.0	Yes	
Date getDate(int columnIndex)	3.0	Yes	
Date getDate(int columnIndex, Calendar cal)	3.0	Yes	
Date getDate(String columnName)	3.0	Yes	
Date getDate(String columnName, Calendar cal)	3.0	Yes	
double getDouble(int columnIndex)	3.0	Yes	
double getDouble(String columnName)	3.0	Yes	
int getFetchDirection()	3.0	Yes	
int getFetchSize()	3.0	Yes	
float getFloat(int columnIndex)	3.0	Yes	
float getFloat(String columnName)	3.0	Yes	
int getHoldability()	4.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
int getInt(int columnIndex)	3.0	Yes	
int getInt(String columnName)	3.0	Yes	
long getLong(int columnIndex)	3.0	Yes	
long getLong(String columnName)	3.0	Yes	
ResultSetMetaData getMetaData()	3.0	Yes	
Reader getNCharacterStream(int columnIndex)	4.0	No	
Reader getNCharacterStream(String columnLabel)	4.0	No	
NClob getNClob(int columnIndex)	4.0	No	
NClob getNClob(String columnLabel)	4.0	No	
String getNString(int columnIndex)	4.0	No	
String getNString(String columnLabel)	4.0	No	
Object getObject(int columnIndex)	3.0	Yes	
<T> T getObject(int columnIndex, Class<T> type)	4.1	No	
Object getObject(int i,	3.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Map<String, Class<?>> map)			
Object getObject(String columnName)	3.0	No	
<T> T getObject(String columnName, Class<T> type)	4.1	No	
Object getObject(String colName, Map<String, Class<?>> map)	3.0	Yes	
Ref getRef(int i)	3.0	No	
Ref getRef(String colName)	3.0	No	
int getRow()	3.0	Yes	
RowId getRowId(int columnIndex)	4.0	No	
RowId getRowId(String columnLabel)	4.0	No	
short getShort(int columnIndex)	3.0	Yes	
short getShort(String columnName)	3.0	Yes	
SQLXML getSQLXML(int columnIndex)	4.0	No	
SQLXML getSQLXML(String columnLabel)	4.0	No	
Statement getStatement()	3.0	Yes	
String getString(int columnIndex)	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>String getString(String columnName)</code>	3.0	Yes	
<code>Time getTime(int columnIndex)</code>	3.0	Yes	
<code>Time getTime(int columnIndex, Calendar cal)</code>	3.0	Yes	
<code>Time getTime(String columnName)</code>	3.0	Yes	
<code>Time getTime(String columnName, Calendar cal)</code>	3.0	Yes	
<code>Timestamp getTimestamp(int columnIndex)</code>	3.0	Yes	
<code>Timestamp getTimestamp(int columnIndex, Calendar cal)</code>	3.0	Yes	
<code>Timestamp getTimestamp(String columnName)</code>	3.0	Yes	
<code>Timestamp getTimestamp(String columnName, Calendar cal)</code>	3.0	Yes	
<code>int getType()</code>	3.0	Yes	
<code>InputStream getUnicodeStream(int columnIndex)</code>	3.0	Yes	Deprecated
<code>InputStream getUnicodeStream(String columnName)</code>	3.0	Yes	Deprecated
<code>URL getURL(int columnIndex)</code>	3.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
URL getURL(String columnName)	3.0	No	
SQLWarning getWarnings()	3.0	Yes	
void insertRow()	3.0	No	Not valid because the driver is read-only.
boolean isAfterLast()	3.0	Yes	
boolean isBeforeFirst()	3.0	Yes	
boolean isClosed()	4.0	Yes	
boolean isFirst()	3.0	Yes	
boolean isLast()	3.0	No	
boolean last()	3.0	No	
void moveToCurrentRow()	3.0	No	Not valid because the driver is read-only.
void moveToInsertRow()	3.0	No	Not valid because the driver is read-only.
boolean next()	3.0	Yes	
boolean previous()	3.0	No	
void refreshRow()	3.0	No	
boolean relative(int rows)	3.0	No	
boolean rowDeleted()	3.0	Yes	Hard-coded to false
boolean rowInserted()	3.0	Yes	Hard-coded to false
boolean rowUpdated()	3.0	Yes	Hard-coded to false

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setFetchDirection(int direction)</code>	3.0	No	Not valid because the driver is forward-only.
<code>void setFetchSize(int rows)</code>	3.0	Yes	
<code>void updateArray(int columnIndex, Array x)</code>	3.0	No	
<code>void updateArray(String columnName, Array x)</code>	3.0	No	
<code>void updateAsciiStream(int columnIndex, InputStream x)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateAsciiStream(int columnIndex, InputStream x, int length)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateAsciiStream(int columnIndex, InputStream x, long length)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateAsciiStream(String columnName, InputStream x)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateAsciiStream(String columnName, InputStream x, int length)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateAsciiStream(String columnName, InputStream x, long length)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateBigDecimal(int columnIndex, BigDecimal x)</code>	3.0	No	Not valid because the driver is read-only.

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void updateBigDecimal (String columnName, BigDecimal x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream (int columnIndex, InputStream x)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream (int columnIndex, InputStream x, int length)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream (int columnIndex, InputStream x, long length)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream (String columnName, InputStream x)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream (String columnName, InputStream x, int length)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream (String columnName, InputStream x, long length)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateBlob(int columnIndex, InputStream inputStream)</code>	4.0	No	
<code>void updateBlob(int columnIndex, Blob x)</code>	3.0	No	
<code>void updateBlob(int columnIndex, InputStream inputStream, long length)</code>	4.0	No	
<code>void updateBlob(String</code>	4.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
columnName, InputStream inputStream)			
void updateBlob(String columnName, Blob x)	3.0	No	
void updateBlob(String columnLabel, InputStream inputStream, long length)	4.0	No	
void updateBoolean(int columnIndex, boolean x)	3.0	No	Not valid because the driver is read-only.
void updateBoolean(String columnName, boolean x)	3.0	No	Not valid because the driver is read-only.
void updateByte(int columnIndex, byte x)	3.0	No	Not valid because the driver is read-only.
void updateByte(String columnName, byte x)	3.0	No	Not valid because the driver is read-only.
void updateBytes(int columnIndex, byte[] x)	3.0	No	Not valid because the driver is read-only.
void updateBytes(String columnName, byte[] x)	3.0	No	Not valid because the driver is read-only.
void updateCharacterStream(int columnIndex, Reader x, int length)	3.0	No	Not valid because the driver is read-only.
void updateCharacterStream(String columnName, Reader reader, int length)	3.0	No	Not valid because the driver is read-only.
void updateBlob(int columnIndex, InputStream inputStream)	4.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void updateClob(int columnIndex, Clob x)</code>	3.0	No	
<code>void updateBlob(int columnIndex, InputStream inputStream, long length)</code>	4.0	No	
<code>void updateBlob(String columnName, InputStream inputStream)</code>	4.0	No	
<code>void updateClob(String columnName, Clob x)</code>	3.0	No	
<code>void updateBlob(String columnName, InputStream inputStream, long length)</code>	4.0	No	
<code>void updateDate(int columnIndex, Date x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateDate(String columnName, Date x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateDouble(int columnIndex, double x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateDouble(String columnName, double x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateFloat(int columnIndex, float x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateFloat(String columnName, float x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateInt(int columnIndex, int x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateInt(String columnName, int x)</code>	3.0	No	Not valid because the driver is read-only.

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void updateLong(int columnIndex, long x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateLong(String columnName, long x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateNCharacterStream(int columnIndex, Reader x)</code>	4.0	No	
<code>void updateNCharacterStream(int columnIndex, Reader x, long length)</code>	4.0	No	
<code>void updateNCharacterStream(String columnName, Reader reader)</code>	4.0	No	
<code>void updateNCharacterStream(String columnName, Reader reader, long length)</code>	4.0	No	
<code>void updateNClob(int columnIndex, NClob nClob)</code>	4.0	No	
<code>void updateNClob(int columnIndex, Reader reader)</code>	4.0	No	
<code>void updateNClob(int columnIndex, Reader reader, long length)</code>	4.0	No	
<code>void updateNClob(String columnName, NClob nClob)</code>	4.0	No	
<code>void updateNClob(String columnName, Reader</code>	4.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
reader)			
void updateNClob(String columnName, Reader reader, long length)	4.0	No	
void updateNString(int columnIndex, String nString)	4.0	No	
void updateNString(String columnName, String nString)	4.0	No	
void updateNull(int columnIndex)	3.0	No	Not valid because the driver is read-only.
void updateNull(String columnName)	3.0	No	Not valid because the driver is read-only.
void updateObject(int columnIndex, Object x)	3.0	No	Not valid because the driver is read-only.
void updateObject(int columnIndex, Object x, int scale)	3.0	No	Not valid because the driver is read-only.
void updateObject(String columnName, Object x)	3.0	No	Not valid because the driver is read-only.
void updateObject(String columnName, Object x, int scale)	3.0	No	Not valid because the driver is read-only.
void updateRef(int columnIndex, Ref x)	3.0	No	Not valid because the driver is read-only.
void updateRef(String columnName, Ref x)	3.0	No	Not valid because the driver is read-only.
void updateRow()	3.0	No	Not valid because the driver is read-only.

Method	Supported Since JDBC Version	Supported by the Driver	Notes
void updateRowId(int columnIndex, RowId x)	4.0	No	
void updateRowId(String columnName, RowId x)	4.0	No	
void updateShort(int columnIndex, short x)	3.0	No	Not valid because the driver is read-only.
void updateShort(String columnName, short x)	3.0	No	Not valid because the driver is read-only.
void updateSQLXML(int columnIndex, SQLXML xmlObject)	4.0	No	
void updateSQLXML(String columnName, SQLXML xmlObject)	4.0	No	
void updateString(int columnIndex, String x)	3.0	No	Not valid because the driver is read-only.
void updateString(String columnName, String x)	3.0	No	Not valid because the driver is read-only.
void updateTime(int columnIndex, Time x)	3.0	No	Not valid because the driver is read-only.
void updateTime(String columnName, Time x)	3.0	No	Not valid because the driver is read-only.
void updateTimestamp(int columnIndex, Timestamp x)	3.0	No	Not valid because the driver is read-only.
void updateTimestamp(String columnName, Timestamp x)	3.0	No	Not valid because the driver is read-only.
boolean wasNull()	3.0	Yes	
boolean isWrapperFor	4.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
(Class<?> iface)			
<T> T unwrap(Class<T> iface)	4.0	Yes	

## ResultSetMetaData

Table 12 lists the methods that belong to the ResultSetMetaData interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the ResultSetMetaData interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/ResultSetMetaData.html>

**Table 12. Methods in the ResultSetMetaData Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
String getCatalogName (int column)	3.0	Yes	
String getColumnClassName (int column)	3.0	Yes	
int getColumnCount ()	3.0	Yes	
int getColumnDisplaySize (int column)	3.0	Yes	
String getColumnLabel (int column)	3.0	Yes	
String getColumnName (int column)	3.0	Yes	
int getColumnType (int column)	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>String getColumnTypeName(int column)</code>	3.0	Yes	
<code>int getPrecision(int column)</code>	3.0	Yes	
<code>int getScale(int column)</code>	3.0	Yes	
<code>String getSchemaName(int column)</code>	3.0	Yes	
<code>String getTableName(int column)</code>	3.0	Yes	
<code>boolean isAutoIncrement(int column)</code>	3.0	Yes	
<code>boolean isCaseSensitive(int column)</code>	3.0	Yes	
<code>boolean isCurrency(int column)</code>	3.0	Yes	
<code>boolean isDefinitelyWritable(int column)</code>	3.0	Yes	
<code>int isNullable(int column)</code>	3.0	Yes	
<code>boolean isReadOnly(int column)</code>	3.0	Yes	
<code>boolean isSearchable(int column)</code>	3.0	Yes	
<code>boolean isSigned(int column)</code>	3.0	Yes	
<code>boolean isWritable(int column)</code>	3.0	Yes	
<code>boolean isWrapperFor</code>	4.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
(Class<?> iface)			
<T> T unwrap(Class<T> iface)	4.0	Yes	

## Statement

Table 13 lists the methods that belong to the Statement interface, and describes whether each method is supported by the Cloudera JDBC Driver for Impala and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the Statement interface, see the Java API documentation available at  
<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/Statement.html>

**Table 13. Methods in the Statement Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
void addBatch(String sql)	3.0	Yes	
void cancel()	3.0	Yes	
void clearBatch()	3.0	Yes	
void clearWarnings()	3.0	Yes	
void close()	3.0	Yes	
void closeOnCompletion()	4.1	Yes	
boolean execute(String sql)	3.0	Yes	
boolean execute(String sql, int autoGeneratedKeys)	3.0	No	
boolean execute(String	3.0	No	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
sql, int[] columnIndexes)			
boolean execute(String sql, String[] columnNames)	3.0	No	
int[] executeBatch()	3.0	No	
ResultSet executeQuery (String sql)	3.0	Yes	
int executeUpdate(String sql)	3.0	Yes	
int executeUpdate(String sql, int autoGeneratedKeys)	3.0	No	
int executeUpdate(String sql, int[] columnIndexes)	3.0	No	
int executeUpdate(String sql, String[] columnNames)	3.0	No	
Connection getConnection ()	3.0	Yes	
int getFetchDirection()	3.0	Yes	
int getFetchSize()	3.0	Yes	
ResultSet getGeneratedKeys()	3.0	Yes	
int getMaxFieldSize()	3.0	Yes	
int getMaxRows()	3.0	Yes	
boolean getMoreResults()	3.0	Yes	
boolean getMoreResults (int current)	3.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
int getQueryTimeout()	3.0	Yes	
ResultSet getResultSet()	3.0	Yes	
int getResultSetConcurrency()	3.0	Yes	Hard-coded to CONCUR_READ_ONLY
int getResultSetHoldability()	3.0	Yes	Hard-coded to CLOSE_CURSORS_AT_COMMIT
int getResultSetType()	3.0	Yes	Hard-coded to TYPE_FORWARD_ONLY
int getUpdateCount()	3.0	Yes	
SQLWarning getWarnings()	3.0	Yes	
boolean isClosed()	4.0	Yes	
boolean isCloseOnCompletion()	4.1	Yes	
boolean isPoolable()	4.0	Yes	
void setCursorName(String name)	3.0	No	
void setEscapeProcessing(boolean enable)	3.0	Yes	
void setFetchDirection(int direction)	3.0	No	
void setFetchSize(int rows)	3.0	Yes	
void setMaxFieldSize(int max)	3.0	Yes	
void setMaxRows(int max)	3.0	Yes	
void setPoolable(boolean	4.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
poolable)			
void setQueryTimeout(int seconds)	3.0	Yes	
boolean isWrapperFor (Class<?> iface)	4.0	Yes	
<T> T unwrap(Class<T> iface)	4.0	Yes	

## Contact Us

If you are having difficulties using the driver, our [Community Forum](#) may have your solution. In addition to providing user to user support, our forums are a great place to share your questions, comments, and feature requests with us.

If you are a Subscription customer you may also use the [Cloudera Support Portal](#) to search the Knowledge Base or file a Case.

**Important:**

To help us assist you, prior to contacting Cloudera Support please prepare a detailed summary of the client and server environment including operating system version, patch level, and configuration.

## Appendix A Configuring Kerberos Authentication for Windows

You can configure your Kerberos setup so that you use the MIT Kerberos Ticket Manager to get the Ticket Granting Ticket (TGT), or configure the setup so that you can use the driver to get the ticket directly from the Key Distribution Center (KDC). Also, if a client application obtains a Subject with a TGT, it is possible to use that Subject to authenticate the connection.

### Downloading and Installing MIT Kerberos for Windows

#### To download and install MIT Kerberos for Windows:

1. To download the Kerberos installer for 64-bit computers, use the following download link from the MIT Kerberos website: <http://web.mit.edu/kerberos/dist/kfw/4.0/kfw-4.0.1- amd64.msi>

The 64-bit installer includes both 32-bit and 64-bit libraries.

OR

To download the Kerberos installer for 32-bit computers, use the following download link from the MIT Kerberos website: <http://web.mit.edu/kerberos/dist/kfw/4.0/kfw-4.0.1- i386.msi>

The 32-bit installer includes 32-bit libraries only.

2. To run the installer, double-click the .msi file that you downloaded in step 1.
3. Follow the instructions in the installer to complete the installation process.
4. When the installation completes, click **Finish**

### Using the MIT Kerberos Ticket Manager to Get Tickets

#### Setting the KRB5CCNAME Environment Variable

You must set the KRB5CCNAME environment variable to your credential cache file.

#### To set the KRB5CCNAME environment variable:

1. Click the **Start** button , then right-click **Computer**, and then click **Properties**
2. Click **Advanced System Settings**
3. In the System Properties dialog box, click the **Advanced** tab, and then click **Environment Variables**
4. In the Environment Variables dialog box, under the System variables list, click **New**
5. In the New System Variable dialog box, in the Variable name field, type **KRB5CCNAME**
6. In the Variable value field, type the path for your credential cache file. For example, type **C:\KerberosTickets.txt**
7. Click **OK** to save the new variable.
8. Ensure that the variable appears in the System variables list.
9. Click **OK** to close the Environment Variables dialog box, and then click **OK** to close the System Properties dialog box.

10. To ensure that Kerberos uses the new settings, restart your computer.

## Getting a Kerberos Ticket

### To get a Kerberos ticket:

1. Click the **Start** button , then click **All Programs**, and then click the **Kerberos for Windows (64-bit)** or **Kerberos for Windows (32-bit)** program group.
2. Click **MIT Kerberos Ticket Manager**
3. In the MIT Kerberos Ticket Manager, click **Get Ticket**
4. In the Get Ticket dialog box, type your principal name and password, and then click **OK**

If the authentication succeeds, then your ticket information appears in the MIT Kerberos Ticket Manager.

## Authenticating to the Impala Server

### To authenticate to the Impala server:

- Use a connection string that has the following properties defined:
- AuthMech
  - KrbHostFQDN
  - KrbRealm
  - KrbServiceName

For detailed information about these properties, see "Driver Configuration Options" on page 79.

## Using the Driver to Get Tickets

### Deleting the KRB5CCNAME Environment Variable

To enable the driver to get Ticket Granting Tickets (TGTs) directly, you must ensure that the KRB5CCNAME environment variable has not been set.

### To delete the KRB5CCNAME environment variable:

1. Click the **Start** button , then right-click **Computer**, and then click **Properties**
2. Click **Advanced System Settings**
3. In the System Properties dialog box, click the **Advanced** tab and then click **Environment Variables**
4. In the Environment Variables dialog box, check if the KRB5CCNAME variable appears in the System variables list. If the variable appears in the list, then select the variable and click **Delete**
5. Click **OK** to close the Environment Variables dialog box, and then click **OK** to close the System Properties dialog box.

## Setting Up the Kerberos Configuration File

### To set up the Kerberos configuration file:

1. Create a standard krb5.ini file and place it in the C:\Windows directory.
2. Ensure that the KDC and Admin server specified in the krb5.ini file can be resolved from your terminal. If necessary, modify "C:\Windows\System32\drivers\etc\hosts".

## Setting Up the JAAS Login Configuration File

### To set up the JAAS login configuration file:

1. Create a JAAS login configuration file that specifies a keytab file and "doNotPrompt=true"

For example:

```
Client {  
    com.sun.security.auth.module.Krb5LoginModule required  
        useKeyTab=true  
        keyTab="PathToTheKeyTab"  
        principal="cloudera@CLOUDERA"  
        doNotPrompt=true;  
};
```

2. Set the java.security.auth.login.config environment variable to the location of the JAAS file.

For example: C:\KerberosLoginConfig.ini

## Authenticating to the Impala Server

### To authenticate to the Impala server:

- Use a connection string that has the following properties defined:
  - AuthMech
  - KrbHostFQDN
  - KrbRealm
  - KrbServiceName

For detailed information about these properties, see "Driver Configuration Options" on page 79.

## Using an Existing Subject to Authenticate the Connection

If the client application obtains a Subject with a TGT, then that Subject can be used to authenticate the connection to the server.

### To use an existing Subject to authenticate the connection:

1. Create a PrivilegedAction for establishing the connection to the database.

For example:

```
// Contains logic to be executed as a privileged action
public class AuthenticateDriverAction
implements PrivilegedAction<Void>
{
    // The connection, which is established as a
    // PrivilegedAction
    Connection con;

    // Define a string as the connection URL
    static String ConnectionURL =
"jdbc:impala://192.168.1.1:21050";

    /**
     * Logic executed in this method will have access to the
     * Subject that is used to "doAs". The driver will get
     * the Subject and use it for establishing a connection
     * with the server.
    */
    @Override
    public Void run()
    {
        try
        {
            // Establish a connection using the connection
            // URL
            con = DriverManager.getConnection(ConnectionURL);
        }
        catch (SQLException e)
        {
            // Handle errors that are encountered during
            // interaction with the data source
            e.printStackTrace();
        }
        catch (Exception e)
        {
            // Handle other errors
        }
    }
}
```

```
        e.printStackTrace();
    }
    return null;
}
}
```

2. Run the PrivilegedAction using the existing Subject, and then use the connection.

For example:

```
// Create the action
AuthenticateDriverAction authenticateAction = new
AuthenticateDriverAction();

// Establish the connection using the Subject for
// authentication.
Subject.doAs(loginConfig.getSubject(), authenticateAction);
// Use the established connection.
authenticateAction.con;
```

## Appendix B Driver Configuration Options

Appendix B lists and describes the properties that you can use to configure the behavior of the Cloudera JDBC Driver for Impala.

**Note:**

You can set configuration properties using the connection URL. For more information, see "Building the Connection URL" on page 7.

### AllowSelfSignedCerts

Default Value	Required
0	No

#### Description

When this property is set to 0, the SSL certificate used by the server cannot be self-signed.

When this property is set to 1, the SSL certificate used by the server can be self-signed.

**Note:**

This property is applicable only when SSL connections are enabled.

### AuthMech

Default Value	Required
0	No

#### Description

The authentication mechanism to use. Set the value to one of the following numbers:

- **0** for No Authentication
- **1** for Kerberos
- **2** for User Name
- **3** for User Name and Password

### CAIssuedCertNamesMismatch

Default Value	Required
0	No

## Description

When this property is set to 0, the name of the CA-issued SSL certificate must match the host name of the Impala server.

When this property is set to 1, the names of the certificate and the host name of the server are allowed to mismatch.

**Note:**

This property is applicable only when SSL connections are enabled.

## CatalogSchemaSwitch

Default Value	Required
0	No

## Description

When this property is set to 1, the driver treats Impala catalogs as schemas as a restriction for filtering.

When this property is set to 0, Impala catalogs are treated as catalogs, and Impala schemas are treated as schemas.

## DefaultStringColumnLength

Default Value	Required
255	No

## Description

The maximum data length for STRING columns. The range of DefaultStringColumnLength is 0 to 32,767.

By default, the columns metadata for Impala does not specify a maximum data length for STRING columns.

## DelegationUID

Default Value	Required
None	No

## Description

Use this option to delegate all operations against Impala to a user that is different than the authenticated user for the connection.

## KrbHostFQDN

Default Value	Required
None	Yes, if AuthMech=1 (Kerberos)

## Description

The fully qualified domain name of the Impala host.

## KrbRealm

Default Value	Required
Depends on Kerberos configuration.	No

## Description

The realm of the Impala host.

If your Kerberos configuration already defines the realm of the Impala host as the default realm, then you do not need to configure this option.

## KrbServiceName

Default Value	Required
None	Yes, if AuthMech=1 (Kerberos)

## Description

The Kerberos service principal name of the Impala server.

## LowerCaseResultSetColumnName

Default Value	Required
1	No

**Description**

When this property is set to 1, the column name aliases in the resultSet metadata are returned in lower-case characters, matching the server-side behavior.

When this property is set to 0, the column name aliases are returned in the same letter case as specified in the query.

**PreparedMetaLimitZero**

Default Value	Required
1	No

**Description**

When this property is set to 1, the PreparedStatement.getMetadata() call will request metadata from the server with "LIMIT 0", increasing performance.

**PWD**

Default Value	Required
None	Yes, if AuthMech=3 (User Name and Password)

**Description**

The password corresponding to the user name that you provided using the property "UID" on page 85.

**RowsFetchedPerBlock**

Default Value	Required
10000	No

**Description**

The maximum number of rows that a query returns at a time.

Any positive 32-bit integer is a valid value, but testing has shown that performance gains are marginal beyond the default value of 10000 rows.

## SocketTimeout

Default Value	Required
0	No

## Description

The number of seconds after which Impala closes the connection with the client application if the connection is idle. The default value of 0 indicates that an idle connection is not closed.

## SSL

Default Value	Required
0	No

## Description

When this property is set to 1, the driver communicates with the Impala server through an SSL-enabled socket.

When this property is set to 0, the driver does not connect to SSL-enabled sockets.

**Note:**

SSL is configured independently of authentication. When authentication and SSL are both enabled, the driver performs the specified authentication method over an SSL connection.

## SSLKeyStore

Default Value	Required
None	Yes, if SSL=1

## Description

The full path and file name of the Java KeyStore containing an SSL certificate to use during authentication.

See also the property "SSLKeyStorePwd" on page 84.

## SSLKeyStorePwd

Default Value	Required
None	Yes, if SSL=1

### Description

The password for accessing the Java KeyStore that you specified using the property "SSLKeyStore" on page 83.

## SSLTrustStore

Default Value	Required
jssecacerts, if it exists.  If jssecacerts does not exist, then cacerts is used. The default location of cacerts is jre\lib\security\	No

### Description

The full path and file name of the Java TrustStore containing an SSL certificate to use during authentication.

See also the property "SSLTrustStorePwd" on page 84.

## SSLTrustStorePwd

Default Value	Required
None	Yes, if using a TrustStore.

### Description

The password for accessing the Java TrustStore that you specified using the property "SSLTrustStore" on page 84.

## UID

Default Value	Required
anonymous	Yes, if AuthMech=3 (User Name and Password) No, if AuthMech=2 (User Name)

## Description

The user name that you use to access the Impala server.

## UseNativeQuery

Default Value	Required
0	No

## Description

When this option is enabled (1), the driver does not transform the queries emitted by an application, so the native query is used.

When this option is disabled (0), the driver transforms the queries emitted by an application and converts them into an equivalent form in Impala SQL.

**Note:**

If the application is Impala-aware and already emits Impala SQL, then enable this option to avoid the extra overhead of query transformation.